

This manual should be considered a permanent part of the vehicle and should remain with the vehicle when it is resold.

This publication includes the latest production information available before printing. Honda Motor Co., Ltd. reserves the right to make changes at any time without notice and without incurring any obligation.

No part of this publication may be reproduced without written permission.

The vehicle pictured in this owner's manual may not match your actual vehicle.

# Welcome

Congratulations on your purchase of a new Honda vehicle. Your selection of a Honda makes you part of a worldwide family of satisfied customers who appreciate Honda's reputation for building quality into every product.

To ensure your safety and riding pleasure:

- Read this owner's manual carefully.
- Follow all recommendations and procedures contained in this manual.
- Pay close attention to safety messages contained in this manual and on the vehicle.

- The following codes in this manual indicate each country.
- The illustrations here in are based on the WW125A KO type.

## Country Codes

---

Code	Country
------	---------

### WW125A

ED	European direct sales, UK, France, Turkey
KO	Korea

---

### WW125

KO	Korea
----	-------

---

\*The specifications may vary with each locale.


## A Few Words About Safety

Your safety, and the safety of others, is very important. Operating this vehicle safely is an important responsibility.

To help you make informed decisions about safety, we have provided operating procedures and other information on safety labels and in this manual. This information alerts you to potential hazards that could hurt you or others.

Of course, it is not practical or possible to warn you about all hazards associated with operating or maintaining a vehicle. You must use your own good judgement.

You will find important safety information in a variety of forms, including:

- Safety labels on the vehicle
- Safety Messages preceded by a safety alert symbol  and one of three signal words: DANGER, WARNING, or CAUTION. These signal words mean:

### **DANGER**

**You WILL be KILLED or SERIOUSLY HURT if you don't follow instructions.**

### **WARNING**

**You CAN be KILLED or SERIOUSLY HURT if you don't follow instructions.**

### **CAUTION**

**You CAN be HURT if you don't follow instructions.**

**Other important information is provided under the following titles:**

#### **NOTICE**

Information to help you avoid damage to your vehicle, other property, or the environment.

# Contents

**Vehicle Safety**

P. 2

**Operation Guide**

P. 18

**Maintenance**

P. 87

**Troubleshooting**

P. 124

**Information**

P. 146

**Specifications**

P. 162

**Index**

P. 165

# Vehicle Safety

This section contains important information for safe riding of your vehicle.  
Please read this section carefully.

Safety Guidelines .....	P. 3
Image Labels .....	P. 6
Safety Precautions .....	P. 10
Riding Precautions .....	P. 11
Accessories & Modifications .....	P. 15
Loading .....	P. 16

## Safety Guidelines

Follow these guidelines to enhance your safety:

- Perform all routine and regular inspections specified in this manual.
- Stop the engine and keep sparks and flame away before filling the fuel tank.
- Do not run the engine in enclosed or partly enclosed areas. Carbon monoxide in exhaust gases is toxic and can kill you.

### Always Wear a Helmet

It's a proven fact: helmets and protective apparel significantly reduce the number and severity of head and other injuries. So always wear an approved helmet and protective apparel. 📄 P. 10

### Before Riding

Make sure that you are physically fit, mentally focused and free of alcohol and drugs. Check

that you and your passenger are both wearing an approved helmet and protective apparel. Instruct your passenger on holding onto the grab rail or your waist, leaning with you in turns, and keeping their feet on the footpegs, even when the vehicle is stopped.

### Take Time to Learn & Practice

Even if you have ridden other vehicles, practice riding in a safe area to become familiar with how this vehicle works and handles, and to become accustomed to the vehicle's size and weight.

### Ride Defensively

Always pay attention to other vehicles around you, and do not assume that other drivers see you. Be prepared to stop quickly or perform an evasive maneuver.

### **Make Yourself Easy to See**

Make yourself more visible, especially at night, by wearing bright reflective clothing, positioning yourself so other drivers can see you, signaling before turning or changing lanes, and using your horn when necessary.

### **Ride within Your Limits**

Never ride beyond your personal abilities or faster than conditions warrant. Fatigue and inattention can impair your ability to use good judgement and ride safely.

### **Don't Drink or Use Drugs and Ride**

Alcohol or drugs and riding don't mix. Even one alcoholic drink can reduce your ability to respond to changing conditions, and your reaction time gets worse with every additional drink. The same is true for drug use. Don't drink

or use and ride, and don't let your friends do it either.

### **Keep Your Honda in Safe Condition**

It's important to keep your vehicle properly maintained and in safe riding condition. Inspect your vehicle before every ride and perform all recommended maintenance. Never exceed load limits (📄 P. 16), and do not modify your vehicle or install accessories that would make your vehicle unsafe (📄 P. 15).

### **If You are Involved in a Crash**

Personal safety is your first priority. If you or anyone else has been injured, take time to assess the severity of the injuries and whether it is safe to continue riding. Call for emergency assistance if needed. Also follow applicable laws and regulations if another person or vehicle is involved in the crash.

If you decide to continue riding, first turn the ignition switch to the **O** (Off) position, and evaluate the condition of your vehicle. Inspect for fluid leaks, check the tightness of critical nuts and bolts, and check the handlebar, control levers, brakes, and wheels. Ride slowly and cautiously.

Your vehicle may have suffered damage that is not immediately apparent. Have your vehicle thoroughly checked at a qualified service facility as soon as possible.

### Carbon Monoxide Hazard

Exhaust contains poisonous carbon monoxide, a colourless, odorless gas. Breathing carbon monoxide can cause loss of consciousness and may lead to death.

If you run the engine in confined or even partly enclosed area, the air you breathe could contain a dangerous amount of carbon monoxide.

Never run your vehicle inside a garage or other enclosure.

### **⚠ WARNING**

Running the engine of your vehicle while in an enclosed or even partially enclosed area can cause a rapid build-up of toxic carbon monoxide gas.

Breathing this colourless, odorless gas can quickly cause unconsciousness and lead to death.

Only run your vehicle's engine when it is located in a well ventilated area outdoors.



## Image Labels

### ED type

The following pages describe the label meanings. Some labels warn you of potential hazards that could cause serious injury. Others provide important safety information. Read this information carefully and don't remove the labels.

If a label comes off or becomes hard to read, contact your dealer for a replacement.

There is a specific symbol on each label. The meanings of each symbol and label are as follows.



Read instructions contained in Owner's Manual carefully.



Read instructions contained in Shop Manual carefully. In the interest of safety, take the vehicle to be serviced only by your dealer.



### **DANGER (with RED background)**

You WILL be KILLED or SERIOUSLY HURT if you don't follow instructions.

### **WARNING (with ORANGE background)**

You CAN be KILLED or SERIOUSLY HURT if you don't follow instructions.

### **CAUTION (with YELLOW background)**

You CAN be HURT if you don't follow instructions.

## BATTERY LABEL DANGER




- Keep flame and spark away from the battery. Battery produce explosive gas that can cause explosion.
- Wear the eye protection and rubber gloves when handling the battery, or you can get burned or lose your eyesight by the battery electrolyte.
- Do not allow children and other people to touch a battery unless they understand proper handling and hazards of the battery very well.
- Handle the battery electrolyte with extreme care as it contains dilute sulfuric acid. Contact with your skin or eyes can burn you or cause loss of your eyesight.
- Read this manual carefully and understand it before handling the battery. Neglect of the instructions can cause personal injury and damage to the vehicle.
- Do not use a battery with the electrolyte at or below the lower level mark. It can explode causing serious injury.



## RADIATOR CAP LABEL DANGER

NEVER OPEN WHEN HOT.  
Hot coolant will scald you.

Relief pressure valve begins to open at **108 kPa**.



## ACCESSORIES AND LOADING WARNING LABEL WARNING

### ACCESSORIES AND LOADING

- The safety stability and handling of this vehicle may be affected by the addition of accessories and luggage.
- Read carefully the instructions contained in user's manual and installation guide before installing any accessory.
- The total weight of accessories and luggage added to rider's and passenger's weight should not exceed **180 kg (397 lb)**, which is the maximum weight capacity.
- The luggage weight must not exceed **13 kg (29 lb)** under any circumstances.
- The fitting of large fork-mounted or large handlebar mounted fairing is not recommended.



## ABS INFORMATION LABEL

This model equipped with an Anti-lock Brake System (ABS) on front wheel.

**TYRE INFORMATION & CARGO LIMIT LABEL**

For your protection, always wear helmet, protective apparel.

Cold tyre pressure:

[Driver only]


Front	<b>200 kPa (2.00 kgf/cm<sup>2</sup>, 29 psi)</b>
Rear	<b>225 kPa (2.25 kgf/cm<sup>2</sup>, 33 psi)</b>

[Driver and passenger]

Front	<b>200 kPa (2.00 kgf/cm<sup>2</sup>, 29 psi)</b>
Rear	<b>250 kPa (2.50 kgf/cm<sup>2</sup>, 36 psi)</b>

Cargo limit:

Front box	<b>1.0 kg (2.2 lb)</b>
Centre compartment	<b>10 kg (22 lb)</b>
Rear carrier	<b>5 kg (11 lb)</b>

**FUEL LABEL**

Unleaded petrol only

ETHANOL up to 10 % by volume

## Safety Precautions

- Ride cautiously and keep your hands on the handlebar and feet on the step board.
- Keep passenger's hands onto the grab rail or your waist, passenger's feet on the footpegs while riding.
- Always consider the safety of your passenger, as well as other drivers and riders.

### Protective Apparel

Make sure that you and any passenger are wearing an approved helmet, eye protection, and high-visibility protective clothing. Avoid wearing loose clothes that could get caught on any part of the vehicle. Ride defensively in response to weather and road conditions.

#### ■ Helmet

Safety-standard certified, high-visibility, correct size for your head

- Must fit comfortably but securely, with the chin strap fastened.

- Face shield with unobstructed field of vision or other approved eye protection

### WARNING

Not wearing a helmet increases the chance of serious injury or death in a crash.

Make sure that you and any passenger always wear an approved helmet and protective apparel.

#### ■ Gloves

Full-finger leather gloves with high abrasion resistance

#### ■ Boots or Riding Shoes

Sturdy boots with non-slip soles and ankle protection

#### ■ Jacket and Trousers

Protective, highly visible, long-sleeved jacket and durable trousers for riding (or a protective suit)

# Riding Precautions

## Running-in Period

During the first 500 km (300 miles) of running, follow these guidelines to ensure your vehicle's future reliability and performance.

- Avoid full-throttle starts and rapid acceleration.
- Avoid hard braking.
- Ride conservatively.

## Brakes

Observe the following guidelines:

- Avoid excessively hard braking.
  - ▶ Sudden braking can reduce the vehicle's stability.
  - ▶ Where possible, reduce speed before turning; otherwise you risk sliding out.

- Exercise caution on low traction surfaces.
  - ▶ The tyres slip more easily on such surfaces and braking distances are longer.
- Avoid continuous braking.
  - ▶ Repeated braking, such as when descending long, steep slopes can seriously overheat the brakes, reducing their effectiveness.
- For full braking effectiveness, operate both the front and rear brakes together.

## Anti-lock Brake System (ABS) on Front Wheel

### WW125A

This model equipped with an Anti-lock Brake System (ABS) designed to help prevent the front brake from locking up during hard braking.

- There is no ABS function to the rear wheel.
- ABS does not reduce braking distance. In certain circumstances, ABS may result in a longer stopping distance.

## Riding Precautions

- ABS does not function at speeds below 10 km/h (6 mph).
- The front brake lever may recoil slightly when applying the brakes. This is normal.
- Always use the recommended front/rear tires to ensure correct ABS operation.

### Combi Brake

#### WW125

Your vehicle is equipped with a brake system that distributes the braking force between the front and rear brakes.

The distribution of the braking force applied to the front and rear brakes when operating the front brake lever only and when operating the rear brake lever only is different.

For full braking effectiveness, operate both the front and rear brakes together.

### Wet or Rainy Conditions

Road surfaces are slippery when wet, and wet brakes further reduce braking efficiency.

Exercise extra caution when braking in wet conditions.

If the brakes get wet, apply the brakes while riding at low speed to help them dry.

### Parking

- Park on a firm, level surface.
- If you must park on a slight incline or loose surface, park so that the vehicle cannot move or fall over.
- Make sure that high-temperature parts cannot come into contact with flammable materials.
- Do not touch the engine, muffler, brakes and other high-temperature parts until they cool down.

- To reduce the likelihood of theft, always lock the handlebar, lock the ignition switch (➤ P. 53) and leave your vehicle while taking the Honda SMART Key with you. Deactivate the Honda SMART Key system if necessary.

➤ P. 48

Use of an anti-theft device is also recommended.

Also set the anti-theft alarm system.

## ■ Parking with the Side Stand or Centre Stand

1. Stop the engine.

### 2. Using the side stand

Push the side stand down.


Slowly lean the vehicle to the left until its weight rests on the side stand.


### Using the centre stand

To lower the centre stand, stand on the left side of the vehicle.

Hold the left handle grip and the grab rail.

Press down on the tip of the centre stand with your right foot and, simultaneously, pull up and back.



3. Turn the handlebar fully to the left.
  - ▶ Turning the handlebar to the right reduces stability and may cause the vehicle to fall.
4. Turn the ignition switch to the  (Lock) position (➤ P. 46) and lock the ignition switch (➤ P. 53).
5. **KO type**  
Set the anti-theft alarm system. ➤ P. 55



## Riding Precautions

### Refuelling and Fuel Guidelines

Follow these guidelines to protect the engine, fuel system and catalytic converter:

- Use only unleaded petrol.
- Use recommended octane number. Using lower octane petrol will result in decreased engine performance.
- Do not use fuels containing a high concentration of alcohol. ➤ P. 160
- Do not use stale or contaminated petrol or an oil/petrol mixture.
- Avoid getting dirt or water in the fuel tank.

### Honda selectable torque control

#### WW125A

When the Honda selectable torque control (Torque Control) detects rear wheel spin during acceleration, the system will limit the amount of torque applied to the rear wheel.

Torque Control does not work during deceleration and will not prevent the rear wheel

from skidding due to engine braking. Do not close the throttle suddenly, especially when riding on slippery surfaces.

Torque Control may not compensate for rough road conditions or rapid throttle operation.

Always consider road and weather conditions, as well as your skills and condition, when applying throttle.

If your vehicle gets stuck in mud, snow or sand, it may be easier to free it by turning off the Torque Control temporarily.

Temporarily turning off Torque Control also may help you maintain control and balance when riding on off-road terrain.

The specified tyres must be used so that the Torque Control can function correctly.

## Accessories & Modifications

We strongly advise that you do not add any accessories that were not specifically designed for your vehicle by Honda or make modifications to your vehicle from its original design. Doing so can make it unsafe. Modifying your vehicle may also void your warranty and make your vehicle illegal to operate on public roads. Before deciding to install accessories on your vehicle be certain the modification is safe and legal.

### **WARNING**

Improper accessories or modifications can cause a crash in which you can be seriously hurt or killed.

Follow all instructions in this owner's manual regarding accessories and modifications.

Do not pull a trailer with, or attach a sidecar to, your vehicle. Your vehicle was not designed for these attachments, and their use can seriously impair your vehicle's handling.

## Loading

- Carrying extra weight affects your vehicle's handling, braking and stability.  
Always ride at a safe speed for the load you are carrying.

- Avoid carrying an excessive load and keep within specified load limits.

**Maximum weight capacity / Maximum luggage weight** ➡ P. 162

- Tie all luggage securely, evenly balanced and close to the centre of the vehicle.
- Do not place objects near the lights or the muffler.

## WARNING

Overloading or improper loading can cause a crash and you can be seriously hurt or killed.


Follow all load limits and other loading guidelines in this manual.



# Basic Operation Flow

## Pre-ride Inspection ➡ P.92

Carefully inspect your vehicle to make sure that it is safe to ride.



How to use basic features.

- Instruments ➡ P.26
- Indicators ➡ P.40
- Switches ➡ P.44
- Steering Lock ➡ P.46
- Honda SMART Key System ➡ P.47
- Anti-theft Alarm System ➡ P.55
- Answer Back System ➡ P.61
- Idling Stop System ➡ P.69

## Acceleration ➡ P.76

Apply throttle gradually.  
Obey the speed limit.



## Starting the Engine ➡ P.73


Start and warm the engine.  
Avoid revving the engine.



## Starting the Vehicle ➡ P.76

Before pulling away, indicate your direction with the turn signal switch, and check for oncoming traffic.



**Braking** ➡ P.77

Close the throttle and apply the front and rear brakes together.


► The brakelight will indicate that you have applied the brakes.

**Stopping**

If pulling off the road, signal early enough to show traffic that you are pulling over, and pull over smoothly.

**Turning Corners**


Do your braking before entering corners.



Gradually reapply throttle when exiting turn.


**Parking** ➡ P.12


Park on a firm level surface.  
Use the stand, lock the steering.

**Refuelling** ➡ P.78

# Parts Location

WW125A ED type









## Parts Location *(Continued)*


WW125A KO type






## Parts Location *(Continued)*

WW125





# Instruments



## Display Check

When the ignition switch is turned **I** (On), initial animation will show.

If any part of these displays does not come on when it should, have your dealer check for problems.

**Clock (12-hour display)**

**To set the clock: ➡ P.33**

**Speedometer**



### Fuel gauge

Remaining fuel when only 1st (E) segment starts flashing approximately: 0.9 L (0.24 US gal, 0.20 Imp gal)

**If the fuel gauge indicator flashes in a repeat pattern or turns off: ➡ P.131**



#### NOTICE

You should refuel when the reading approaches the 1st (E) segment. Running out of fuel can cause the engine to misfire, damaging the catalytic converter.

## Instruments (Continued)



### Odometer [TOTAL] , Tripmeter [TRIP] & Torque Control [HSTC]

**SEL** switch selects the odometer, tripmeter and Torque Control.

- Odometer:  
Total distance ridden.
- Tripmeter:  
Distance ridden since tripmeter was reset.  
To reset tripmeter, press and hold **SET** switch with tripmeter displayed.  
The average fuel mileage is also reset.

#### WW125A

Torque Control :


Pressing and holding **SET** switch while Torque Control is displayed turns Torque Control on and off. ➡ P.72

### Average fuel mileage meter [AVG]

The average fuel mileage will be based on tripmeter.

Average fuel mileage since tripmeter was reset.

When " -.- " is displayed except after the average fuel mileage has been reset, go to your dealer for service.



### OIL CHANGE indicator

The indicator is turned on whenever the running distance reaches the programmed oil change interval.

When the running distance reaches about 1,000 km (600 miles):

Reset the indicator for the 1st time.

When the running distance reaches about every 6,000 km (4,000 miles) after the 1st time resetting:

Reset the indicator whenever it is turned on.

After changing the engine oil, be sure to reset the indicator.


The indicator does not go off until it is reset.

If the oil is changed before the oil change indicator comes on, be sure to reset the oil change indicator after changing the oil.

**How to Reset the OIL CHANGE Indicator:** ➡ P.36



## Instruments (Continued)



### V-BELT indicator

#### KO type

The indicator turns on when the running distance reaches the set distance.

The indicator turns on when the running distance reaches about 12,000 km (8,000 miles) since the last reset.

Reset the indicator whenever it is turned on. After inspecting or replacing the belt, be sure to reset the indicator.

The indicator does not go off until it is reset. If the belt is inspected or replaced before the V-BELT indicator comes on, be sure to reset the indicator after inspecting or replacing the belt.

### How to Reset the V-BELT Indicator:

➡ P.38

## Display Setting


Following items can be changed sequentially.

- Clock setting
- Backlight brightness adjustment
- **ED type**  
Changing of speed and mileage unit
- Changing of fuel mileage meter unit
- Resetting OIL CHANGE indicator
- **KO type**  
Resetting V-BELT indicator


⇨ Press and hold **SEL** switch and **SET** switch

➡ Press **SET** switch

⇩ Press **SEL** switch



## Instruments (Continued)



The following moves the ordinary display at display setting.

- The switch is not pressed for about 30 seconds
  - ▶ The items that are being set are deleted, and only the items whose settings have been completed are reflected.
- Turn the ignition switch to the **○** (Off) position and then to the **I** (On) position
  - ▶ The items that are being set and the items whose settings have been completed are reflected.

## 1 Clock setting:

- ① Turn the ignition switch to the **I** (On) position.
- ② Pressing and holding **SEL** switch and **SET** switch makes the hour and minute displays start flashing.
- ③ Press **SET** switch, the hour digits start flashing.
- ④ Press **SEL** switch until the desired hour is displayed.
  - ▶ Press and hold to advance the hour fast.



- ⑤ Press **SET** switch. The minute digits start flashing.



- ⑥ Press **SEL** switch until the desired minute is displayed.

▶ Press and hold to advance the minute fast.



- ⑦ Press **SET** switch. The clock is set, and then the display moves to the backlight brightness adjustment. (backlight brightness indicator and backlight brightness adjustment segments start flashing.)

## Instruments (Continued)

### 2 Backlight brightness adjustment:

You can adjust the brightness to one of five levels.

- 1 Press **SET** switch, the backlight brightness indicator and backlight brightness adjustment segments flash faster.
- 2 Press **SEL** switch. The brightness is switched.



### 3 ED type

Press **SET** switch. The backlight is set, and then the display moves to the changing of speed and mileage unit. (speed and mileage unit start flashing.)


#### KO type

Press **SET** switch. The backlight is set, and then the display moves to the changing of the fuel mileage meter unit. (fuel mileage meter unit start flashing.)

### 3 Changing of speed and mileage unit:

#### ED type

- 1 Press **SET** switch, the speed and mileage unit start flashing fast.
- 2 Press **SEL** switch to select either "km/h" and "km" or "mph" and "mile".



- 3 Press **SET** switch. The speed and mileage unit is set, and then the display moves to the changing of fuel mileage meter unit. (fuel mileage meter unit start flashing.)

#### 4 Changing the fuel mileage meter unit:

- 1 Press **SET** switch, the fuel mileage meter unit start flashing fast.
- 2 Press **SEL** switch to select "km/L" or "L/100km".

**km/L** ↔ **L/100km**

##### ED type

If the "mph" for speed and "mile" for mileage are selected, the fuel mileage shown by "mile/L" or "mile/gal".

**mile/gal** ↔ **mile/ L**


- 3 Press **SET** switch. The fuel mileage meter unit is set, and then the display moves to running distance until OIL CHANGE indicator lights. (OIL CHANGE indicator starts flashing.)

#### 5 Running distance until OIL CHANGE indicator lights display:

You can confirm the running distance until the OIL CHANGE indicator lights, and then reset the OIL CHANGE indicator.

##### Confirming the running distance until OIL CHANGE indicator lights

Display the running distance until the OIL CHANGE indicator lights.





**Running distance until OIL CHANGE indicator lights**



## Instruments (Continued)

### Resetting OIL CHANGE indicator

- 1 Pressing **SET** switch causes the OIL CHANGE indicator, and the running distance until the OIL CHANGE indicator lights, to flash.
  - ▶ "P" flashes when the running distance until the OIL CHANGE indicator lights is displayed.



- 2 Press **SEL** switch to select oil change interval.
  - ▶ "P" turns off when the oil change interval is displayed.
  - ▶ When the running distance until the OIL CHANGE indicator lights is displayed, the OIL CHANGE indicator does not reset even if **SET** switch is pressed.



**3 ED type**

Pressing **SET** switch resets the OIL CHANGE indicator. When this is reset, the display changes to normal.

**KO type**


Pressing the **SET** switch resets the OIL CHANGE indicator. When this is reset, the display changes to the running distance until V-BELT indicator lights. (V-BELT indicator starts flashing.)

**6 Running distance until V-BELT indicator lights display:****KO type**

You can confirm the running distance until the V-BELT indicator lights, and then reset the V-BELT indicator.

**Confirming the running distance until V-BELT indicator lights**

Display the running distance until the V-BELT indicator lights.





**Running distance until  
V-BELT indicator lights**



## Instruments (Continued)



### Resetting V-BELT indicator

- Pressing **SET** switch causes the V-BELT indicator, and the running distance until the V-BELT indicator lights, to flash.
- "P" flashes when the running distance until V-BELT indicator lights is displayed.



- Press **SEL** switch to select maintenance interval.


- "P" turns off when the maintenance interval is displayed.
- When the running distance until the V-BELT indicator lights is displayed, the V-BELT indicator does not reset even if **SET** switch is pressed.




- 3 Pressing **SET** switch resets the V-BELT indicator. When this is reset, the display changes to normal.


# Indicators

If one of these indicators does not come on when it should, have your dealer check for problems.





## Indicators (Continued)



### Torque Control indicator

**WW125A**

- Comes on when the ignition switch is turned to the **I** (On) position.
- Goes off when your speed reaches approximately 3 km/h (2 mph) to indicate Torque Control is ready to work.
- Blinks when Torque Control is operating.

**If it comes on while riding: ➡ P.129**



### Torque Control OFF indicator

**WW125A**

Comes on when the Torque Control is turned to off.



### ABS (Anti-lock Brake System) indicator


**WW125A**

Comes on when the ignition switch is turned to the **I** (On) position.  
Goes off when your speed reaches approximately 10 km/h (6 mph).

**If it comes on while riding: ➡ P.128**



# Switches



## Turn signal switch

- ▶ Pressing the switch turns the turn signal off.



## Horn button

## Headlight dimmer switch

- ☰ : High beam
- ☷ : Low beam

## Idling stop switch

- Ⓐ : The Idling Stop system is on.
- Ⓐ<sub>OFF</sub> : The Idling Stop system is off.

**Idling Stop system:** ➡ P.69



## Hazard switch

The hazard signal is on.  
Switchable when the ignition switch is on.



## Start button

## **Ignition switch**

Switches the electrical system on/off, locks the steering, and operates the fuel lid and seat opener switch.

**To unlock the ignition switch:**


 **P.52**

**I (On)**  
Turns electrical system on for starting/riding.

**SEAT FUEL**  
Operates the fuel lid and seat opener switch.

**O (Off)**  
Turns engine off.

**(Lock)**  
Locks steering.






## Switches *(Continued)*


### Steering Lock

Lock the steering when parking to help prevent theft.

A U-shaped wheel lock or similar device is also recommended.




### Locking

- 1 Turn the handlebar all the way to the left or right.
- 2 Push the ignition switch down, and turn it to the  (Lock) position.
  - ▶ To unlock the ignition switch ➡ **P.52**
  - ▶ Jiggle the handlebar if the lock is difficult to engage.
- 3 Lock the ignition switch.

### Unlocking

Push the ignition switch in, and turn it to the

 (Off) position.

- ▶ To unlock the ignition switch ➡ **P.52**

# Honda SMART Key System

The Honda SMART Key system allows you to operate the ignition switch without inserting a key into a keyhole.

The system runs a two-way authentication between the vehicle and the Honda SMART Key to verify if it is the registered Honda SMART Key.

The Honda SMART Key system uses low-intensity radio waves. It may affect medical equipment such as a cardiac pacemaker.

## Honda SMART Key System *(Continued)*

### Switching the Honda SMART Key System

#### **To switch the Honda SMART Key system to activation or deactivation**

Press the ON/OFF button until the Honda SMART Key LED changes colour.

#### **To check the Honda SMART Key system status**


Lightly press the ON/OFF button. The Honda SMART Key LED will show the status.

When the Honda SMART Key LED is:

- Green: Honda SMART Key system authentication can be performed.
- Red: Honda SMART Key system authentication cannot be performed.

ED type


LED



ON/OFF button

KO type

LED



ON/OFF button

## Operating Range


The operating range varies when the ignition switch is locked or unlocked.

The Honda SMART Key system uses low-intensity radio waves. Therefore, the operating range may be wider or narrower, or the Honda SMART Key system may not work properly in the following situations:

- When the Honda SMART Key battery is depleted.
- When there are facilities nearby that generate strong radio waves or noise, such as TV towers, power stations, radio stations, or airports.
- When you carry the Honda SMART Key with a laptop or wireless communication device such as a radio or mobile phone.
- When the Honda SMART Key comes into contact with or is covered by metal objects.

## When the ignition switch is unlocked:


The system can be operated within the shaded area shown in the illustration.



## Honda SMART Key System *(Continued)*


### When the ignition switch is locked:

The system can be operated within the shaded area shown in the illustration.



Anyone can unlock the ignition switch and start the engine if your Honda SMART Key is within operating range of your vehicle, even if you are on the other side of a wall or window. If you are away from your vehicle but your Honda SMART Key is still within operating range, deactivate the Honda SMART Key system.

**To switching the Honda SMART Key system** ➡ **P.48**



Anyone in possession of the Honda SMART Key can perform the following operations if the Honda SMART Key is within operating range:

- Starting the engine
- Unlocking the ignition switch
- Releasing the seat lock
- Opening the fuel lid
- Unlocking the steering lock

You should always keep the Honda SMART Key on your person after you get on and off the vehicle or while riding.

Do not store the Honda SMART Key in any compartment.

If the ignition switch is in the **I** (On) position, the vehicle can be operated even by a person who does not have a verified Honda SMART Key.

Whenever you leave your vehicle, lock the steering and lock the ignition switch.



Make sure the ignition switch ring goes off and all turn signals flash once at this time.

## Honda SMART Key System (Continued)


### Switching the ignition switch

#### To Unlock the Ignition Switch

- 1 Make sure that the Honda SMART Key is activated. ➡ **P.48**
- 2 To authenticate the Honda SMART Key system, push the ignition switch.
  - ▶ When properly authenticated and the ignition switch is unlocked, the Honda SMART Key indicator and ignition switch ring come on.
  - KO type** The buzzer also rings 2 times at this time.
  - ▶ **KO type** The buzzer sound can be cancelled. ➡ **P.54**
- 3 Turn the ignition switch to the **I** (On) position while the Honda SMART Key indicator comes on.
  - ▶ If you do not turn the ignition switch to the **I** (On) position within 20 seconds after pushing in the ignition switch in, the Honda SMART Key indicator and ignition switch ring will go off, the turn signals flash 1 time, and then the ignition switch will be locked.

### When the Honda SMART Key system does not work properly ➡ **P.135**

If someone without the Honda SMART Key tries to turn the ignition switch, the ignition switch rotates freely. If you notice the ignition switch is in a different position, turn the ignition switch to the original (**O** (Off) or **i** (Lock)) position.





## To Lock the Ignition Switch

- 1 Turn the ignition switch to the SEAT FUEL, ○ (Off) or 🔒 (Lock) position.
- 2 Lock the ignition switch by doing one of the following:
  - Leave the operating range with the Honda SMART Key. ➡ P.49
  - Push the ignition switch.
  - Wait for approximately 20 seconds after turning the ignition switch from | (On) to SEAT FUEL, ○ (Off) or 🔒 (Lock) position.
  - Switch the Honda SMART Key system to inactive. ➡ P.48
- 3 Make sure that the Honda SMART Key indicator and ignition switch ring go off and the turn signals flash once. This indicates that the ignition switch is locked.
 

**KO type** The buzzer also rings 1 time at this time.



► **KO type** The buzzer sound can be cancelled. ➡ P.54


When the Honda SMART Key system does not work properly ➡ P.135






## Honda SMART Key System *(Continued)*

Always make sure the ignition switch position is in the  (Off) or  (Lock) position when you leave your vehicle.

When the ignition switch is locked in the SEAT FUEL position, the ignition switch can be turned  (Off) position only once.

When the ignition switch is locked in the  (Off) position, the steering cannot be locked. To lock the steering, unlock the ignition switch.

### Switch the Buzzer Sound When the Ignition Switch is Locked/Unlocked

KO type

#### Enable



- 1 Deactivate the Honda SMART Key system.  
➡ **P.48**
- 2 Lightly press the ON/OFF button. The red Honda SMART Key LED comes on.
- 3 While the red LED is on, press the answer back/alarm button.
  - ▶ The red LED starts blinking when the buzzer sound is properly enabled.

#### Disable

- 1 Deactivate the Honda SMART Key system.  
➡ **P.48**
- 2 Lightly press the ON/OFF button. The red Honda SMART Key LED blinks.
- 3 While the red LED is blinking, press the answer back/alarm button.
  - ▶ The red LED stops blinking but stays on when the buzzer sound is properly disabled.



# Anti-theft Alarm System

## KO type


The anti-theft alarm system is a device to reduce the likelihood of theft. When the sensor detects vibration or movement with the ignition switch in the  (Off) or  (Lock) position and the system is set, the alarm is activated.


The buzzer rings and the turn signals blink for about 10 seconds when the anti-theft alarm system detects vibration caused by contact or movement.

The buzzer rings and the turn signals blink for about 60 seconds when the anti-theft alarm system detects a substantial change in the vehicle posture. After the buzzer rings for 60 seconds, the anti-theft alarm system will be reset in that posture.



## Anti-theft Alarm System *(Continued)*



If the ignition switch is left  (Off) for more than 10 days, the anti-theft alarm system will no longer operate. When the system is active and the vehicle receives a signal from pressing the answer back/alarm button, system activation will be extended for 10 days.

To reset the system, turn the ignition switch to the  (On) position once.

The anti-theft alarm system uses low-intensity radio waves. It may affect medical equipment such as a cardiac pacemaker.

When the battery in the vehicle is weak, the anti-theft alarm system may not function.


## Setting the Anti-theft Alarm System

- 1 Turn the ignition switch to  (Off) or  (Lock) position.
- 2 Press the answer back/alarm button. Within a second, the turn signal light blinks and the buzzer rings 1 time. After 2.5 seconds, the buzzer rings 1 time. The anti-theft alarm system is activated. The alarm indicator flashes while the anti-theft alarm system is activated.

### Answer back/ alarm button



### Alarm indicator



## ■ Cancelling the Anti-theft Alarm System

To cancel the anti-theft alarm system, unlock the ignition switch. ➡ **P.52**


When the ignition switch is unlocked, the buzzer rings 2 times and the alarm indicator goes off.

## ■ Stopping the Anti-theft Alarm Activation

To stop the anti-theft alarm activation, do one of the following:

- Press the answer back/alarm button on the Honda SMART Key.
  - ▶ After stopping the anti-theft alarm activation, the anti-theft alarm system will be reset.
- Unlock the ignition switch. ➡ **P.52**
  - ▶ After stopping the anti-theft alarm activation, the anti-theft alarm system will be cancelled.

**Answer back/  
alarm button**



## Anti-theft Alarm System *(Continued)*

### Adjusting the Sensitivity of Anti-theft Alarm System


You can select from 3 sensitivity levels for the anti-theft alarm system.

- ① Make sure that the Honda SMART Key system is active. ➡ **P.48**
- ② Push the ignition switch to authenticate the Honda SMART Key system. ➡ **P.52**
- ③ Press and hold the ignition switch for more than 4 seconds.
  - ▶ The Honda SMART Key indicator and ignition switch ring flash.

#### Answer back/ alarm button



#### Ignition switch



#### Ignition switch ring

- ④ Press the ignition switch 1 time while the Honda SMART Key indicator and ignition switch ring are flashing.
  - ▶ The Honda SMART Key indicator and ignition switch ring come on, and a buzzer sounds.
- ⑤ Repeat the following 3 times:  
Press the answer back/alarm button on the Honda SMART Key 4 times and the ignition switch 1 time.

- ▶ When the ignition switch is pressed, the Honda SMART Key indicator and ignition switch ring go off, and the buzzer sounds. When they light again, do the next input.
  - ▶ When the answer back/alarm button is pressed, the Honda SMART Key LED comes on. Make sure the LED goes off before pressing the button again.
  - ▶ When the answer back/alarm button or ignition switch is not pressed for 1 minute, the Honda SMART Key indicator and ignition switch ring flash 3 times, and then the buzzer sounds and the mode is cancelled. Return to ❸ and do the procedure again.
  - ▶ If you press the answer back/alarm button the wrong number of times before you repeat the procedure 3 times, then repeat the procedure 3 times again.
- ❹ Press the answer back/alarm button to select from 3 sensitivity levels.  
3 alarm rings: high sensitivity  
2 alarm rings: medium sensitivity  
1 alarm ring: low sensitivity  
The Honda SMART Key indicator and ignition switch ring come on while setting.
  - ❺ Press and hold the ignition switch for more than 2 seconds. The sensitivity level is set.
    - ▶ The Honda SMART Key indicator and ignition switch ring turn off, and a buzzer sounds once.
    - ▶ When the answer back/alarm button is not pressed for 10 seconds, the Honda SMART Key indicator and ignition switch ring flash 3 times, and then the buzzer sounds, and the sensitivity level is set.

## **Anti-theft Alarm System** *(Continued)*

### **If the Anti-Theft Alarm System Does Not Operate Properly**

If any of the following situations arise, the battery (➡P.103) in the vehicle may be discharged or there is a system problem. Remove the battery and see your dealer.

- The alarm does not ring.
- The alarm rings but fades out.
- The alarm system does not stop.


# Answer Back System

## ED type

The answer back system is a device to find the location of your vehicle.

When the immobilizer is active and you press the answer back button on the Honda SMART Key with the ignition switch in the ○ (Off) or 🔒 (Lock) position, the turn signals light, and the ignition switch ring lights, informing you of your vehicle's location. The ignition switch ring will light for about 1 minute.

The answer back system uses low-intensity radio waves. It may affect medical equipment such as a cardiac pacemaker.








## Answer Back System *(Continued)*


### Operation


Press the answer back button on the Honda SMART Key.

- ▶ The answer back system will not function when the ignition switch is  (On) position.

If the ignition switch is left in the  (Off) or  (Lock) position for more than 10 days, the answer back system will no longer operate.

When the system is active and the vehicle receives a signal from pressing the answer back button, system activation will be extended for 10 days.

To reset the system, turn the the ignition switch to the  (On) position once.

- ▶ To unlock the ignition switch  **P.52**


When the battery in the vehicle is weak, the answer back system may not function.

### KO type

The answer back system is a device to find the location of your vehicle.

When the immobilizer is active and you press the answer back/alarm button on the Honda SMART Key with the ignition switch in the ○ (Off) or 🔒 (Lock) position, the turn signals light, and the ignition switch ring lights, informing you of your vehicle's location. The ignition switch ring will light for about 1 minute.

The answer back system uses low-intensity radio waves. It may affect medical equipment such as a cardiac pacemaker.



## Answer Back System *(Continued)*

### Operation

Press the answer back/alarm button on the Honda SMART Key.

- ▶ The answer back system will not function when the ignition switch is **I** (On) position.

If the ignition switch is left the **O** (Off) or **LOCK** (Lock) position for more than 10 days, the answer back system will no longer operate. When the system is active and the vehicle receives a signal from pressing the answer back/alarm button, system activation will be extended for 10 days.

To reset the system, turn the the ignition switch to the **I** (On) position once.

- ▶ To unlock the ignition switch ➡ **P.52**

When the battery in the vehicle is weak, the answer back system may not function.

### Adjusting the Answer Back Buzzer Sound Volume Level


You can select 3 buzzer sound volume levels.

- 1 Make sure that the Honda SMART Key system is active. ➡ **P.48**
- 2 Push the ignition switch to authenticate the Honda SMART Key system. ➡ **P.52**
- 3 Press and hold the ignition switch for more than 4 seconds.
  - ▶ The Honda SMART Key indicator and ignition switch ring flash.

#### Answer back/ alarm button



#### Ignition switch



#### Ignition switch ring

- 4 Press the ignition switch 1 time while the Honda SMART Key indicator and ignition switch ring are flashing.
  - ▶ The Honda SMART Key indicator and ignition switch ring come on, and a buzzer sounds.
- 5 Repeat the following 3 times:  
Press the answer back/alarm button on the Honda SMART Key 2 times and the ignition switch 1 time.
  - ▶ When the ignition switch is pressed, the Honda SMART Key indicator and ignition switch ring go off, and the buzzer sounds. When they light again, do the next input.
  - ▶ When the answer back/alarm button is pressed, the Honda SMART Key LED comes on. Make sure the LED goes off before pressing the button again.
  - ▶ When the answer back/alarm button or ignition switch is not pressed for 1 minute, the Honda SMART Key indicator and ignition switch ring flash 3 times, and then the buzzer sounds and the mode is cancelled. Return to 3 and do the procedure again.
- ▶ If you press the answer back/alarm button the wrong number of times before you repeat the procedure 3 times, then repeat the procedure 3 times again.
- 6 Press the answer back/alarm button to select from 3 levels for the sound volume. The Honda SMART Key indicator and ignition switch ring come on while setting.

## Answer Back System *(Continued)*

- 7 Press and hold the ignition switch for more than 2 seconds. The sound volume level is set.
  - ▶ The Honda SMART Key indicator and ignition switch ring turn off, and a buzzer sounds once.
  - ▶ When the answer back/alarm button is not pressed for 10 seconds, the Honda SMART Key indicator and ignition switch ring flash 3 times, and then the buzzer sounds, and the sound volume level is set.

## Changing the Answer Back Buzzer Sound Pattern


You can select 3 buzzer sound patterns.

- 1 Make sure that the Honda SMART Key system is active. ➡ **P.48**
- 2 Push the ignition switch to authenticate the Honda SMART Key system. ➡ **P.52**
- 3 Press and hold the ignition switch for more than 4 seconds.
  - ▶ The Honda SMART Key indicator and ignition switch ring flash.

### Answer back/ alarm button



### Ignition switch



### Ignition switch ring

- 4 Press the ignition switch 1 time while the Honda SMART Key indicator and ignition switch ring are flashing.

► The Honda SMART Key indicator and ignition switch ring come on, and a buzzer sounds.

- 5 Repeat the following 3 times:

Press the answer back/alarm button on the Honda SMART Key 3 times and the ignition switch 1 time.

► When the ignition switch is pressed, the Honda SMART Key indicator and ignition switch ring go off, and the buzzer sounds. When they light again, do the next input.

► When the answer back/alarm button is pressed, the Honda SMART Key LED comes on. Make sure the LED goes off before pressing the button again.

► When the answer back/alarm button or ignition switch is not pressed for 1 minute, the Honda SMART Key indicator

and ignition switch ring flash 3 times, and then the buzzer sounds and the mode is cancelled. Return to 3 and do the procedure again.

► If you press the answer back/alarm button the wrong number of times before you repeat the procedure 3 times, then repeat the procedure 3 times again.

- 6 Press the answer back/alarm button to select from 3 buzzer sound patterns. The Honda SMART Key indicator and ignition switch ring come on while setting.

## Answer Back System *(Continued)*

- 7 Press and hold the ignition switch for more than 2 seconds. The sound pattern is set.
  - ▶ The Honda SMART Key indicator and ignition switch ring turn off, and a buzzer sounds once.
  - ▶ When the answer back/alarm button is not pressed for 10 seconds, the Honda SMART Key indicator and ignition switch ring flash 3 times, and then the buzzer sounds, and the sound pattern is set.

### **Temporary Silence Mode**

Temporary silence mode is the immediate way to turn off the answer back system buzzer sound.

#### **Enable:**

Press and hold the answer back/alarm button for about 2 seconds, the Honda SMART Key LED changes to red.

#### **Disable:**

Re-press and hold the answer back/alarm button for about 2 seconds, the Honda SMART Key LED changes to green.

# Idling Stop System

Idling Stop system is designed to help reduce the fuel consumption and noise, by idling stop while making a stop such as waiting at an intersection.

## Switching the Idling Stop System On or Off

Switches the Idling Stop system on or off using the Idling Stop switch.

### ● ON: (A) (Idling Stop)

- ▶ Idling Stop indicator comes on when the Idling Stop system becomes ready to stop the engine while riding. Idling Stop indicator flashes when the engine is stopped by the Idling Stop system.

### ● OFF: (A) OFF (Idling)

- ▶ Idling Stop indicator does not come on when the Idling Stop system is off.

## Activation of the Idling Stop System


The Idling Stop system becomes ready to stop the engine and Idling Stop indicator comes on when the following requirements are satisfied with the Idling Stop switch in the (A) (Idling Stop) position:

- side stand is up
- start the engine by pressing the start button
- warm up the engine enough
- ride the vehicle at speeds over 10 km/h (6 mph)


## Idling Stop Indicator Does Not Come On:

➡ P.132

Idling Stop switch



Idling Stop indicator






## Idling Stop System *(Continued)*

### Stopping the engine by the Idling Stop System


The engine stops and Idling Stop indicator changes to flash after you close the throttle completely and stop the vehicle while the Idling Stop indicator is on.

- ▶ While the engine is stopped by the Idling Stop system, if you press the Idling Stop switch to  (Idling), the Idling Stop system will be cancelled. The engine will not restart even when you open the throttle.



**Idling Stop indicator**

### Safety Precaution for the Idling Stop System

Do not go away from the vehicle while the Idling Stop indicator is flashing. When you go away from the vehicle, always turn the ignition switch to the  (Off) position.

- ▶ The engine may start unexpectedly if the throttle is opened.

### **Engine is Not Stopped by the Idling Stop System While the Idling Stop Indicator is On: P.133**

#### **NOTICE**

Stopping by the Idling Stop system for a long time may cause battery discharge.

### Restarting the Engine


Check that the Idling Stop indicator is flashing, and then open the throttle.

- ▶ If it is not flashing, you can't restart the engine with the Idling Stop system, even if you open the throttle.
- ▶ While the engine is stopped by the Idling Stop system, if you operate the side stand, the flashing Idling Stop indicator turns off or stops flashing and stays on, then the engine will not restart even when you open the throttle.

**Engine Does Not Start Even If the Throttle is Opened:** ➡ P.134

#### NOTICE

Headlight stays on after the engine is stopped by the Idling Stop system. The battery may discharge and you may not be able to restart engine.

When the battery is weak, switch the Idling Stop switch to  (Idling) and do not to use the Idling Stop system. See your dealer to check the battery.

See your dealer for checking the battery as specified in the maintenance schedule.

**Maintenance Schedule:** ➡ P.89


# Honda selectable torque control

## WW125A

Torque Control (engine power control) can be turned on/off.


- ▶ Stop the vehicle first, turn the Torque Control off or on.
- ▶ The Torque Control cannot be turned off when the system is activated (Torque Control indicator blinking).
- ▶ Each time the ignition switch is turned to the **I** (On) position, the Torque Control will automatically be set to on.

### Torque Control OFF indicator



### Torque Control on and off

Press **[SEL]** switch to display the Torque Control [HSTC]. Pressing and holding **[SET]** switch while Torque Control [HSTC] is displayed switches between on and off.



# Starting the Engine

Start your engine using the following procedure, regardless of whether the engine is cold or warm.

This vehicle is equipped with a side stand ignition cut-off system.

- ▶ If the side stand is down, the engine cannot be started.
- ▶ If you lower the side stand with the engine running, it will automatically shut off.

This vehicle is equipped with a Honda SMART Key system. Always keep Honda SMART Key on you when you ride the vehicle. ➡ **P.49**

If the engine of this vehicle is stopped while the ignition switch is in the **I** (On) position, authentication will be disabled after a certain amount of time or if you leave the authentication range. Restart the engine by performing step **3** & **4** under the starting procedure.


- ▶ If the engine of this vehicle is stopped by the Idling Stop System, authentication will not be disabled.

## NOTICE


- If the engine does not start within 5 seconds, turn the ignition switch to the **O** (Off) position and wait 10 seconds before trying to start the engine again to recover battery voltage.
- Extended fast idling and revving the engine can damage the engine, and the exhaust system.
- If the vehicle is over-turned, you must first turn the ignition switch to the **O** (Off) position and then inspect the vehicle carefully.

## Starting the Engine (Continued)

- 1 Place the vehicle on its centre stand.
- 2 Turn the ignition switch to the **I** (On) position.
  - ▶ To unlock the ignition switch. ➡ **P.52**




- 3 Squeeze the rear brake lever.
  - ▶ The starter motor will only work when the rear brake lever is squeezed and the side stand is up.
- 4 Press the start button with the throttle completely closed. Release the start button as soon as the engine starts.



**If you cannot start the engine:**

- ① Place the vehicle on its centre stand and squeeze the rear brake lever.
- ② With the throttle slightly open (about 3 mm, without freeplay), press the start button.

**About 3 mm, without freeplay**

**If the engine does not start:**

- ① Open the throttle fully and press the start button for 5 seconds.
- ② Repeat the normal starting procedure.
- ③ If the engine starts, open the throttle slightly if idling is unstable.
- ④ If the engine does not start, wait 10 seconds before trying steps ① & ② again.

**If Engine Will Not Start ➡ P.125**

# Riding

## Starting the Vehicle


- 1 Push the vehicle forward off the center stand.

- ▶ Squeeze the rear brake lever.
- ▶ Keep throttle closed.

Make sure the side stand and centre stand are up.


- 2 Get on the vehicle.
  - ▶ Mount the vehicle from the left side, keeping at least one foot on the ground.
- 3 Release the brake lever.

- 4 Acceleration and deceleration  
To accelerate: Open the throttle slowly.  
To decelerate: Close the throttle.



## Braking

Close the throttle and apply the front and rear brake levers together.





# Refuelling

**Fuel type:** Unleaded petrol only


**Fuel octane number:** Your vehicle is designed to use Research Octane Number (RON) 91 or higher.

**Tank capacity:** 8.1 L (2.14 US gal, 1.78 Imp gal)


**Refuelling and Fuel Guidelines** ➔ P.14

## Opening the Fuel Fill Cap

- 1 Turn the ignition switch to the position of SEAT FUEL.  
▶ To unlock the ignition switch ➔ P.52
- 2 Push the FUEL side of the fuel lid and seat opener switch.  
▶ The fuel lid opens.




- 3 Turn the fuel fill cap counterclockwise and remove the fuel fill cap.



- 4 Put the removed fuel fill cap on the fuel fill cap resting place.

**Fuel fill cap resting place**



Do not fill with fuel above the lower edge of the filler neck.

## Refuelling *(Continued)*

### Closing the Fuel Fill Cap

- ① Install and tighten the fuel fill cap firmly by turning it clockwise.
  - ▶ Make sure that the arrow marks on the fuel fill cap and fuel tank are aligned.
- ② Close the fuel lid until it locks.
  - ▶ Make sure that the fuel lid is closed securely.

### **WARNING**

Petrol is highly flammable and explosive. You can be burned or seriously injured when handling fuel.

- Stop the engine, and keep heat, sparks, and flame away.
- Handle fuel only outdoors.
- Wipe up spills immediately.

# USB Socket

The USB socket is located in the front box.

## ➡ P.85

Use USB devices at your own risk. In no event shall Honda be liable for any damage to your USB device when in use.


Open the cover to access the USB socket.

USB type-C connectors can be used.

Rated capacity is

**15 W (5 V, 3.0 A).**

▶ The USB socket is for charging only.




- ▶ To prevent the battery from becoming weak (or dead), keep the engine running while drawing current from the USB socket.
- ▶ To prevent entry of foreign matter into the USB socket, be sure to close the cover when the USB socket is not used.

### NOTICE

- Using any heat-generating USB devices or improperly rated USB devices can damage the USB socket.
- Do not use the USB socket in wet conditions, when or while washing or any other wet conditions as these will damage the USB socket.
- Do not allow the USB's harness to become pinched or trapped.

# Storage Equipment

## Seat



## Seat Open

- ① Turn the handlebar pointed straight ahead.
- ② Turn the ignition switch to the position of SEAT FUEL.  
▶ To unlock the ignition switch ➡ P.52
- ③ Push the SEAT side of the fuel lid and seat opener switch.
- ④ Open the seat.


## Seat Close

Close and push down on the rear of the seat until it locks. Make sure that the seat is locked securely by pulling it up lightly. Take care not to lock your key in the compartment under the seat.

## Helmet Holder

The helmet holder is located under the seat.

- Use the helmet holder only when parked.



## **⚠ WARNING**

Riding with a helmet attached to the holder can interfere with your ability to safely operate the vehicle and could lead to a crash in which you can be seriously hurt or killed.


Use the helmet holder only while parked. Do not ride with a helmet secured by the holder.

## Storage Equipment *(Continued)*

A helmet can be stored in the centre compartment.

Set in the front of the helmet forward.

- Some helmets may not fit in the compartment due to their size or design.



### Centre compartment


Never exceed the maximum weight limit.

#### Maximum Weight: 10 kg (22 lb)


- Do not store any items that are flammable or susceptible to heat damage.
- Do not store valuables or fragile articles.

## Tool Kit/Document Bag

The tool kit and document bag are located underside of the seat by the rubber strap.



## Front Box



### | Open

Push the front box lid, then open the front box lid.

### | Close

Close the front box lid by pressing the front box lid.

The maximum allowable load in the front box shall be no more than

**1.0 kg (2.2 lb)**

Make sure that the front box lid is closed securely.

► Do not store valuables or fragile articles.




## **Storage Equipment** *(Continued)*

### **Rear Carrier**

Never exceed the maximum weight limit.

**Rear carrier**



**Maximum Weight: 5 kg (11 lb)**

# Maintenance

Please read "Importance of Maintenance" and "Maintenance Fundamentals" carefully before attempting any maintenance. Refer to "Specifications" for service data.

<b>Importance of Maintenance .....</b>	<b>P. 88</b>
<b>Maintenance Schedule.....</b>	<b>P. 89</b>
<b>Maintenance Fundamentals .....</b>	<b>P. 92</b>
<b>Tool.....</b>	<b>P. 102</b>
<b>Removing &amp; Installing Body</b>	
<b>Components .....</b>	<b>P. 103</b>
Battery.....	P. 103
Battery Cover .....	P. 104
Front Lid .....	P. 105
<b>Engine Oil.....</b>	<b>P. 106</b>
<b>Coolant .....</b>	<b>P. 108</b>
<b>Brakes.....</b>	<b>P. 110</b>
<b>Side Stand .....</b>	<b>P. 119</b>
<b>Throttle .....</b>	<b>P. 120</b>

<b>Other Replacement.....</b>	<b>P. 121</b>
Replacing the Honda SMART Key Battery ..	P. 121

# Importance of Maintenance

## Importance of Maintenance

Keeping your vehicle well-maintained is absolutely essential to your safety and to protect your investment, obtain maximum performance, avoid breakdowns, and reduce air pollution. Maintenance is the owner's responsibility. Be sure to inspect your vehicle before each ride, and perform the periodic checks specified in the Maintenance Schedule.

➤ P. 89

### WARNING


Improperly maintaining your vehicle or failing to correct a problem before you ride can cause a crash in which you can be seriously hurt or killed.

Always follow the inspection and maintenance recommendations and schedules in this owner's manual.

## Maintenance Safety

Always read the maintenance instructions before you begin each task, and make sure that you have the tools, parts, and skills required. We cannot warn you of every conceivable hazard that can arise in performing maintenance. Only you can decide whether or not you should perform a given task.

Follow these guidelines when performing maintenance.

- Stop the engine and turn the ignition switch to the  (Off) position.
- Place your vehicle on a firm, level surface using the side stand, centre stand or a maintenance stand to provide support.
- Allow the engine, muffler, brakes, and other high-temperature parts to cool before servicing as you can get burned.
- Run the engine only when instructed, and do so in a well-ventilated area.

## Maintenance Schedule

The maintenance schedule specifies the maintenance requirements necessary to ensure safe, dependable performance, and proper emission control.

Maintenance work should be performed in accordance with Honda's standards and specifications by properly trained and equipped technicians. Your dealer meets all of these requirements. Keep an accurate record of maintenance to help ensure that your vehicle is properly maintained.

Make sure that whomever performs the maintenance completes this record.

All scheduled maintenance is considered a normal owner operating cost and will be charged to you by your dealer. Retain all receipts. If you sell the vehicle, these receipts should be transferred with the vehicle to the new owner.

Honda recommends that your dealer should road test your vehicle after each periodic maintenance is carried out.

## Maintenance Schedule







Items		Pre-ride Check P. 92	Frequency *1								Annual Check	Regular Replace	Refer to page
			× 1,000 km	1	6	12	18	24	30	36			
			× 1,000 mi	0.6	4	8	12	16	20	24			
Fuel Line	🔧				I	I	I	I	I	I	I		–
Fuel Level		I											78
Throttle Operation	🔧	I			I	I	I	I	I	I	I		120
Air Cleaner *2	🔧						R			R			–
Crankcase Breather *3					C	C	C	C	C	C			–
Spark Plug					I	R	I	R	I	R			–
Valve Clearance	🔧				I	I	I	I	I	I			–
Engine Oil		I		R	R	R	R	R	R	R	R		–
Engine Oil Strainer Screen						C		C		C			–
Engine Idle Speed	🔧				I	I	I	I	I	I	I		–
Radiator Coolant *4		I				I		I		I	I	3 Years	108
Cooling System	🔧					I		I		I	I		–
Evaporative Emission Control System	🔧						I			I			–
Drive Belt	🔧					I		R		I			–
Final Drive Oil *4	🔧											2 Years	–

### Maintenance Level

- 🔧 : Intermediate. We recommend service by your dealer, unless you have the necessary tools and are mechanically skilled.  
Procedures are provided in an official Honda Shop Manual.
- 🔧 : Technical. In the interest of safety, have your vehicle serviced by your dealer.

### Maintenance Legend

- I : Inspect (clean, adjust, lubricate, or replace, if necessary)  
R : Replace  
C : Clean

Items		Pre-ride Check P. 92	Frequency *1								Annual Check	Regular Replace	Refer to page
			× 1,000 km	1	6	12	18	24	30	36			
			× 1,000 mi	0.6	4	8	12	16	20	24			
Battery					I	I	I	I	I	I	I		103
Brake Fluid *4		I			I	I	I	I	I	I	I	2 Years	110
Brake Pads Wear (Rear Brake Disk type)		I			I	I	I	I	I	I	I		113
Brake Shoes/Pads Wear (Rear Brake Drum type)		I			I	I	I	I	I	I	I		114, 118
Brake System (Rear Brake Disk type)					I	I	I	I	I	I	I		92
Brake System (Rear Brake Drum type)		I			I	I	I	I	I	I	I		92
Headlight Aim					I	I	I	I	I	I	I		–
Lights/Horn		I											–
Clutch Shoes Wear						I		I		I			–
Side Stand		I			I	I	I	I	I	I	I		119
Suspension					I	I	I	I	I	I	I		–
Nuts, Bolts, Fasteners						I		I		I	I		–
Wheels/Tyres		I			I	I	I	I	I	I	I		99
Steering Head Bearings						I		I		I	I		–

**Notes:**

\*1 : At higher odometer reading, repeat at the frequency interval established here.

\*2 : Service more frequently when riding in unusually wet or dusty areas.

\*3 : Service more frequently when riding in rain or at full throttle.

\*4 : Replacement requires mechanical skill.

## Pre-ride Inspection

To ensure safety, it is your responsibility to perform a pre-ride inspection and make sure that any problem you find is corrected. A pre-ride inspection is a must, not only for safety, but because having a breakdown, or even a flat tyre, can be a major inconvenience.

Check the following items before you get on your vehicle:

- Fuel level - Fill fuel tank when necessary. ➔ P. 79
- Throttle - Check for smooth opening and full closing in all steering positions. ➔ P. 120
- Engine oil level - Add engine oil if necessary. Check for leaks. ➔ P. 106
- Coolant level - Add coolant if required. Check for leaks. ➔ P. 108

- Brakes - Check operation;

### WW125A KO type

Front and Rear: check brake fluid level and pads wear. ➔ P. 110, ➔ P. 113

### WW125

Front: check brake fluid level and pads wear. ➔ P. 111, ➔ P. 114

Combi Brake: check brake fluid level. ➔ P. 111

Rear: check shoes wear and freeplay, adjust if necessary. ➔ P. 115, ➔ P. 118

### WW125A ED type

Front: check brake fluid level and pads wear. ➔ P. 112, ➔ P. 114


Rear: check shoes wear and freeplay, adjust if necessary. ➔ P. 115, ➔ P. 118

- Lights and horn - Check that lights, indicators and horn function properly.
- Side stand ignition cut-off system - Check for proper function. ➔ P. 119
- Wheels and tyres - Check condition, air pressure and adjust if necessary. ➔ P. 99

## Replacing Parts

Always use Honda Genuine Parts or their equivalents to ensure reliability and safety. When ordering coloured components, specify the model name, colour, and code mentioned on the colour label.

The colour label is attached to the centre compartment. ➤ P. 84



## ⚠ WARNING

Installing non-Honda parts may make your vehicle unsafe and cause a crash in which you can be seriously hurt or killed.

Always use Honda Genuine Parts or equivalents that have been designed and approved for your vehicle.



### Battery

Your vehicle has a maintenance-free type battery. You do not have to check the battery electrolyte level or add distilled water. Clean the battery terminals if they become dirty or corroded.

Do not remove the battery cap seals. There is no need to remove the cap when charging.

#### NOTICE

Your battery is a maintenance-free type and can be permanently damaged if the cap strip is removed.

#### ED type



This symbol on the battery means that this product must not be treated as household waste.

#### NOTICE

An improperly disposed of battery can be harmful to the environment and human health. Always confirm local regulations for proper battery disposal instruction.

### What to do in an emergency

If any of the following occur, immediately see your doctor.

- Electrolyte splashes into your eyes:
  - ▶ Wash your eyes repeatedly with cool water for at least 15 minutes. Using water under pressure can damage your eyes.
- Electrolyte splashes onto your skin:
  - ▶ Remove affected clothing and wash your skin thoroughly using water.
- Electrolyte splashes into your mouth:
  - ▶ Rinse mouth thoroughly with water, and do not swallow.

**⚠ WARNING**


The battery gives off explosive hydrogen gas during normal operation.

A spark or flame can cause the battery to explode with enough force to kill or seriously hurt you.

Wear protective clothing and a face shield, or have a skilled mechanic do the battery servicing.

**Cleaning the Battery Terminals**

1. Remove the battery. ➡ P. 103
2. If the terminals are starting to corrode and are coated with a white substance, wash with warm water and wipe clean.
3. If the terminals are heavily corroded, clean and polish the terminals with a wire brush or sandpaper. Wear safety glasses.



4. After cleaning, reinstall the battery.

The battery has a limited life span. Consult your dealer about when you should replace the battery. Always replace the battery with another maintenance-free battery of the same type.

**NOTICE**


Installing non-Honda electrical accessories can overload the electrical system, discharging the battery and possibly damaging the system.

## Maintenance Fundamentals

### Fuses

Fuses protect the electrical circuits on your vehicle. If something electrical on your vehicle stops working, check for and replace any blown fuses. ➤ P. 143

#### Inspecting and Replacing Fuses

Turn the ignition switch to the  (Off) position to remove and inspect fuses. If a fuse is blown, replace with a fuse of the same rating. For fuse ratings, see "Specifications." ➤ P. 164

Blown fuse



#### NOTICE

Replacing a fuse with one that has a higher rating greatly increases the chance of damage to the electrical system.

If a fuse fails repeatedly, you likely have an electrical fault. Have your vehicle inspected by your dealer.

### Engine Oil

Engine oil consumption varies and oil quality deteriorates according to riding conditions and time elapsed.

Check the engine oil level regularly, and add the recommended engine oil if necessary. Dirty oil or old oil should be changed as soon as possible.


#### Selecting the Engine Oil

For recommended engine oil, see "Specifications." ➤ P. 163


If you use non-Honda engine oil, check the label to make sure that the oil satisfies all of the following standards:

- JASO T 903 standard\*1: MB
- SAE standard\*2: 10W-30
- API classification\*3: SG or higher

- \*1. The JASO T 903 standard is an index for engine oils for 4-stroke motorcycle engines. There are two classes: MA and MB. For example, the following label shows the MB classification.



- \*2. The SAE standard grades oils by their viscosity.  
 \*3. The API classification specifies the quality and performance rating of engine oils. Use SG or higher oils, excluding oils marked as "Energy Conserving" or "Resource Conserving" on the circular API service symbol.



## Brake Fluid

Do not add or replace brake fluid, except in an emergency. Use only fresh brake fluid from a sealed container. If you do add fluid, have the brake system serviced by your dealer as soon as possible.

### NOTICE

Brake fluid can damage plastic and painted surfaces.  
 Wipe up spills immediately and wash thoroughly.

### Recommended brake fluid:

Honda DOT 3 or DOT 4 Brake Fluid or equivalent

### Recommended Coolant

Pro Honda HP Coolant is a pre-mixed solution of antifreeze and distilled water.

#### **Concentration:**

50% antifreeze and 50% distilled water

A concentration of antifreeze below 40% will not provide proper corrosion and cold temperature protection.

A concentration of up to 60% will provide better protection in colder climates.

#### **NOTICE**

Using coolant not specified for aluminium engines or tap/mineral water can cause corrosion.

### Crankcase Breather

Service more frequently when riding in rain, at full throttle, or after the vehicle is washed or overturned. Service if the deposit level can be seen in the transparent section of the drain tube.


If the drain tube overflows, the air filter may become contaminated with engine oil causing poor engine performance.

## Tyres (Inspecting/Replacing)

### ■ Checking the Air Pressure

Visually inspect your tyres and use an air pressure gauge to measure the air pressure at least once a month or any time you think the tyres look low. Always check air pressure when your tyres are cold.


### ■ Inspecting for Damage



Inspect the tyres for cuts, slits, or cracks that exposes fabric or cords, or nails or other foreign objects embedded in the side of the tyre or the tread.

Also inspect for any unusual bumps or bulges in the side walls of the tyres.


### ■ Inspecting for Abnormal Wear



Inspect the tyres for signs of abnormal wear on the contact surface.

### Inspecting Tread Depth

Inspect the tread wear indicators. If they become visible, replace the tyres immediately.



### **⚠ WARNING**

Riding on tyres that are excessively worn or improperly inflated can cause a crash in which you can be seriously hurt or killed.

Follow all instructions in this owner's manual regarding tyre inflation and maintenance.

Have your tyres replaced by your dealer.  
For recommended tyres and air pressure, see  
"Specifications." 📄 P. 163

Follow these guidelines whenever you replace  
tyres.

- Use the recommended tyres or equivalents  
of the same size, construction, speed rating,  
and load range.
- Do not install a tube inside a tubeless tyre  
on this vehicle. Excessive heat build-up can  
cause the tube to burst.
- Use only tubeless tyres on this vehicle.  
The rims are designed for tubeless tyres,  
and during hard acceleration or braking, a  
tube-type tyre could slip on the rim and  
cause the tyre to rapidly deflate.

## **WARNING**

Installing improper tyres on your  
vehicle can adversely affect handling  
and stability, and can cause a crash in  
which you can be seriously hurt or  
killed.

Always use the size and type of tyres  
recommended in this owner's manual.



The tool kit is stored underside of the seat.

➔ P. 84

You can perform some roadside repairs, minor adjustments and parts replacement with the provided tools.


## ED type

- 10 × 14 mm Open end wrench
- Standard/Phillips screwdriver
- Screwdriver handle

## KO type

- Spark plug wrench
- 10 × 14 mm Open end wrench
- Standard/Phillips screwdriver
- Screwdriver handle

## Battery



### Removal

Make sure the ignition switch is in the **Off** position.

1. Remove the battery cover. ➤ P. 104
2. Unhook the rubber strap.
3. Disconnect the negative  $\ominus$  terminal from the battery.

4. Disconnect the positive  $\oplus$  terminal from the battery.
5. Remove the battery taking care not to drop the terminal nuts.

### Installation

Install the parts in the reverse order of removal.

Always connect the positive  $\oplus$  terminal first. Make sure that bolts and nuts are tight.

Make sure the clock information is correct after the battery is reconnected. ➤ P. 33


#### KO type

The anti-theft alarm system will be deactivated if the battery is disconnected. The system will remain off when the battery is reconnected.

To activate the system, turn the ignition switch to the **On** position once.

For proper handling of the battery, see "Maintenance Fundamentals." ➤ P. 94  
"Battery Goes Dead." ➤ P. 142

## Battery Cover



### Removal

1. Open the seat. ► P. 82
2. Press the tabs and remove the battery cover.

### Installation

Install the parts in the reverse order of removal.

## Front Lid



### Removal

Pull out the front lid backward while pushing the side of the front lid.

### Installation

Install the part in the reverse order of removal.


Make sure that all tabs are installed securely in position.



## Checking the Engine Oil

Check the engine oil with the Idling Stop switch at **A** (Idling).  
OFF

1. If the engine is cold, idle the engine for 3 to 5 minutes.
2. Turn the ignition switch to the **O** (Off) position and wait for 2 to 3 minutes.
3. Place your vehicle on its centre stand on a firm, level surface.
4. Remove the oil fill cap/dipstick and wipe it clean.
5. Insert the oil fill cap/dipstick until it seats, but don't screw it in.
6. Check that the oil level is between the upper level and lower level marks on the oil fill cap/dipstick.
7. Securely install the oil fill cap/dipstick.



## Adding Engine Oil

If the engine oil is below or near the lower level mark, add the recommended engine oil.

► P. 96, ► P. 163

1. Remove the oil fill cap/dipstick. Add the recommended oil until it reaches the upper level mark.
  - Place your vehicle on its centre stand on a firm, level surface when checking the oil level.
  - Do not overfill above the upper level mark.
  - Make sure no foreign objects enter the oil filler opening.
  - Wipe up any spills immediately.
2. Securely reinstall the oil fill cap/dipstick.

### NOTICE

Overfilling with oil or operating with insufficient oil can cause damage to your engine. Do not mix different brands and grades of oil.


For the recommended oil and oil selection guidelines, see "Maintenance Fundamentals."

► P. 96

## Checking the Coolant

Check the coolant level in the reserve tank while the engine is cold.

1. Place your vehicle on its centre stand on a firm, level surface.
2. Check that the coolant level is between the UPPER level and LOWER level marks on the reserve tank.



If the coolant level is dropping noticeably or the reserve tank is empty, you likely have a serious leak. Have your vehicle inspected by your dealer.

## Adding Coolant

If the coolant level is below the LOWER level mark, add the recommended coolant (► P. 98) until the level reaches the UPPER level mark.

Add fluid only from the reserve tank cap and do not remove the radiator cap.


1. Pull the floor mat off.
2. Remove the reserve tank lid by inserting a flat head screwdriver covered with a protective cloth into the slit on the right side floor.

3. Remove the reserve tank cap and add fluid while monitoring the coolant level.
  - Do not overfill above the UPPER level mark.
  - Make sure no foreign objects enter the reserve tank opening.
4. Securely reinstall the reserve tank cap.
5. Install the reserve tank lid and floor mat.

## **⚠ WARNING**

Removing the radiator cap while the engine is hot can cause the coolant to spray out, potentially scalding you.

Always let the engine and radiator cool down before removing the radiator cap.






## Checking Brake Fluid

### WW125A KO type

1. Place your vehicle in an upright position on a firm, level surface.
2. Check that the brake fluid reservoir is horizontal and that the fluid level is above the LWR mark.

If the brake fluid level in either reservoir is below the LWR mark or both the brake levers freeplay becomes excessive, inspect the brake pads for wear.

If the brake pads are not worn, you most likely have a leak. Have your vehicle inspected by your dealer.




**WW125**

1. Place your vehicle in an upright position on a firm, level surface.
2. Check that the brake fluid reservoir is horizontal and that the fluid level is:  
**Front brake** above the LWR mark.  
**Combi brake** between the LOWER level and UPPER level marks.

If the brake fluid level in either reservoir is below the LWR mark or LOWER level mark or the brake lever freeplay becomes excessive, inspect the brake pads for wear.

If the brake pads are not worn, you most likely have a leak. Have your vehicle inspected by your dealer.




## Checking the Front Brake Fluid

### WW125A ED type

1. Place your vehicle in an upright position on a firm, level surface.
2. Check that the brake fluid reservoir is horizontal and that the fluid level is above the LWR mark.

If the brake fluid level in the reservoir is below the LWR mark or the brake lever freeplay becomes excessive, inspect the brake pads for wear.

If the brake pads are not worn, you most likely have a leak. Have your vehicle inspected by your dealer.



## Inspecting the Brake Pads

### WW125A KO type

Check the condition of the brake pad wear indicators.


**Front** The pads need to be replaced if a brake pad is worn to the bottom of the indicator.

**Rear** The pads need to be replaced if a brake pad is worn to the indicator.

1. **Front** Inspect the brake pads from in front of the brake caliper.
2. **Rear** Inspect the brake pads from the rear right of the vehicle.

If necessary have the pads replaced by your dealer.

Always replace both left and right brake pads at the same time.



## Inspecting the Front Brake Pads

### WW125, WW125A ED type


Check the condition of the brake pad wear indicators.

The pads need to be replaced if a brake pad is worn to the bottom of the indicator.

1. Inspect the brake pads from in front of the brake caliper.

If necessary have the pads replaced by your dealer.

Always replace both left and right brake pads at the same time.




## Inspecting the Rear Brake Lever Freeplay

WW125, WW125A ED type

1. Place the vehicle on its centre stand.
2. Measure the distance the rear brake lever moves before the brake takes hold.

### Freeplay at the tip of the brake lever:

10 - 20 mm (0.4 - 0.8 in)




Check the brake cable for kinks or signs of wear. If necessary have it replaced by your dealer.

Lubricate the brake cable with a commercially available cable lubricant to prevent premature wear and corrosion. Make sure the brake arm, spring and fastener are in good condition.

## Adjusting the Rear Brake Lever Freeplay


WW125, WW125A ED type

Adjust the freeplay of the brake lever with the front wheel pointed straight ahead. Make sure the cut-out on the adjusting nut is seated on the brake arm pin when adjusting the freeplay.




If proper adjustment cannot be obtained by this method, see your dealer.

1. Adjust by turning the rear brake adjusting nut a half-turn at a time.



2. Apply the brake several times and check for free wheel rotation after the brake lever is released.

3. Push the brake arm to confirm that there is a gap between the rear brake adjusting nut and brake arm pin.



After adjustment, confirm the freeplay of the brake lever.

Make sure the brake arm, spring and fastener are in good condition.

**NOTICE**


Do not turn the adjuster beyond its natural limits.



## Inspecting the Rear Brake Shoe Wear

WW125, WW125A ED type


The rear brake is equipped with a brake wear indicator.



When the brake is applied, an arrow attached to the brake arm moves toward a reference mark on the brake panel. If the arrow aligns with the reference mark on full application of the brake, the brake shoes must be replaced. See your dealer for this service.

When the brake service is necessary, see your dealer. Use only Honda Genuine Parts or its equivalent.

### Checking the Side Stand




1. Place your vehicle on its centre stand on a firm, level surface.
2. Check that the side stand operates smoothly. If the side stand is stiff or squeaky, clean the pivot area and lubricate the pivot bolt with clean grease.
3. Check the spring for damage or loss of tension.
4. Sit on the vehicle and raise the side stand.
5. Start the engine.
6. Lower the side stand all the way. The engine should stop as you lower the side stand. If the engine doesn't stop, have your vehicle inspected by your dealer.

## Checking the Throttle

With the engine off, check that the throttle rotates smoothly from fully closed to fully open in all steering positions and throttle freeplay is correct. If the throttle does not move smoothly, close automatically, or if the cable is damaged, have the vehicle inspected by your dealer.

### Freeplay at the throttle grip flange:

2 - 6 mm (0.1 - 0.2 in)



### Replacing the Honda SMART Key Battery


---

If the Honda SMART Key indicator flashes 5 times when the ignition switch is turned **I** (On), or the operating range becomes unstable, replace the battery as soon as possible.

We recommend to see your dealer for this service.

<b>Battery type:</b> CR2032
-----------------------------

1. Remove the upper case by inserting a coin or a flat head screwdriver covered with a protective cloth into the slit.
  - ▶ Wrap a coin or a screwdriver with a protective cloth to prevent scratching the Honda SMART Key.
  - ▶ Do not touch the circuit or terminal. This may cause problems.
  - ▶ Be careful to avoid scratching the waterproof covering or allowing dust to enter.
  - ▶ Do not forcibly dismantle the Honda SMART Key body.



2. Replace the old battery with a new battery with the negative  $\ominus$  side facing up.
3. Snap the two halves of the Honda SMART Key back together.
  - Make sure that upper and lower cases are set in the right position.

## ⚠ WARNING

**Chemical Burn Hazard: do not swallow battery.**

If swallowed, the battery can cause severe internal burns and even death.

- Keep battery away from children and battery compartment securely closed.
- If the battery compartment does not close securely, stop using the product and keep it away from children.
- Immediately seek medical attention if a child may have swallowed battery.

**CAUTION:** Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type.

**CAUTION:** Do not exposed to excessive heat such as sunshine, fire or the like, that can result in an explosion or the leakage of flammable liquid or gas during use, storage or transportation.

**CAUTION:** Do not dispose of a battery into fire or a hot oven, or give mechanically crushing or cutting of a battery, that can result in an explosion.

**CAUTION:** Do not subjected to extremely low air pressure at high altitude that may result in an explosion or the leakage of flammable liquid or gas.

# Troubleshooting

<b>Engine Will Not Start</b> .....	P. 125
<b>Overheating (High coolant temperature indicator is on)</b> .....	P. 126
<b>Warning Indicators On or Flashing</b> .....	P. 127
PGM-FI (Programmed Fuel Injection)	
Malfunction Indicator Lamp (MIL).....	P. 127
Battery Charging Condition indicator .....	P. 127
ABS (Anti-lock Brake System) Indicator .....	P. 128
Torque Control Indicator.....	P. 129
Honda SMART Key Indicator.....	P. 130
<b>Other Warning Indications</b> .....	P. 131
Fuel Gauge Failure Indication.....	P. 131
<b>When the Idling Stop System Does Not Operate Properly</b> .....	P. 132
Idling Stop Indicator Does Not Come On ..	P. 132

Engine is Not Stopped by the Idling Stop System While the Idling Stop Indicator is On.....	P. 133
Engine Does Not Start Even If the Throttle is Opened .....	P. 134
<b>When the Honda SMART Key System Does Not Operate Properly</b> .....	P. 135
<b>Unlock the Seat in an Emergency</b> .....	P. 137
<b>Unlock the Ignition Switch in an Emergency</b> .....	P. 138
<b>Tyre Puncture</b> .....	P. 141
<b>Electrical Trouble</b> .....	P. 142
Battery Goes Dead.....	P. 142
Burned-out Light Bulb .....	P. 142
Blown Fuse .....	P. 143
<b>Unstable Engine Operation Occurs Intermittently</b> .....	P. 145

### **Starter Motor Operates But Engine Does Not Start**

---

Check the following items:

- Check the correct engine starting sequence. ➡ P. 73
- Check that there is petrol in the fuel tank.
- Check if the PGM-FI malfunction indicator lamp (MIL) is on.
  - ▶ If the indicator lamp is on, contact your dealer as soon as possible.

### **Starter Motor Does Not Operate**

---

Check the following items:

- Check the correct engine starting sequence. ➡ P. 73
- Check for a blown fuse. ➡ P. 143
- Check for a loose battery connection (➡ P. 103) or battery terminal corrosion (➡ P. 94).
- Check the condition of the battery.
  - ➡ P. 142

If the problem continues, have your vehicle inspected by your dealer.



## Overheating (High coolant temperature indicator is on)


The engine is overheating when the following occurs:

- High coolant temperature indicator comes on.
- Acceleration becomes sluggish.

If this occurs, pull safely to the side of the road and perform the following procedure. Extended fast idling may cause the high coolant temperature indicator to come on.

### NOTICE

Continuing to ride with an overheated engine can cause serious damage to the engine.

1. Stop the engine using the ignition switch.
2. Allow the engine to cool with the ignition switch in the  (Off) position.
3. After the engine has cooled, inspect the radiator hose and check if there is a leak.  
➡ P. 108  
**If there is a leak:**  
Do not start the engine. Transport your vehicle to your dealer.
4. Check the coolant level in the reserve tank. ➡ P. 108  
▶ Add coolant as necessary.
5. If 1-4 check normal, you may continue riding, but closely monitor the high coolant temperature indicator.

### **PGM-FI (Programmed Fuel Injection) Malfunction Indicator Lamp (MIL)**

---

If the indicator comes on while riding, you may have a serious problem with the PGM-FI system. Reduce speed and have your vehicle inspected by your dealer as soon as possible.

### **Battery Charging Condition indicator**

---

If the indicator comes on while riding, you may have a condition of low battery voltage or battery performance degradation. Have your vehicle inspected by your dealer.

- ▶ If the battery does not have enough voltage to drive the indicator system, the indicator may not come on.

## ABS (Anti-lock Brake System) Indicator

---

### WW125A

If the indicator operates in one of the following ways, you may have a serious problem with the ABS. Reduce your speed and have your vehicle inspected by your dealer as soon as possible.

- Indicator comes on or starts flashing while riding.
- Indicator does not come on when the ignition switch is turned to the **I** (On) position.
- Indicator does not go off at speeds above 10 km/h (6 mph).

If the ABS indicator stays on, your brakes will continue to work as a conventional system, but without the anti-locking function.

The ABS indicator may flash if you turn the rear wheel while the rear wheel is lifted off the ground. In this case, turn the ignition switch to the **O** (Off) position, and then to the **I** (On) position again. The ABS indicator will go off after your speed reaches 30 km/h (19 mph).

## Torque Control Indicator

### WW125A

If the indicator operates in one of the following ways, you may have a serious problem with the Torque Control. Reduce your speed and have your vehicle inspected by your dealer as soon as possible.

- Indicator comes and stays on (solid) while riding.
- Indicator does not come on when the ignition switch is turned to the **I** (On) position.
- Indicator does not go off at speeds above 3 km/h (2 mph).

Even when the Torque Control indicator is on, your vehicle will have normal riding ability without Torque Control function.

- When the indicator comes on while the Torque Control is in operation, you will have to completely close the throttle to regain normal riding ability.

The Torque Control indicator may come on if you rotate the rear wheel while your vehicle is lifted off the ground. In this case, turn the ignition switch to the **O** (Off) position, and then to the **I** (On) position again. The Torque Control indicator will go off after your speed reaches 3 km/h (2 mph).

## Honda SMART Key Indicator

### When the Honda SMART Key indicator flashes 5 times

**Replacing the Honda SMART Key Battery** ■ P. 121

### When the Honda SMART Key indicator is flashing while the ignition switch is in the (On) position

The Honda SMART Key indicator flashes when communication between your vehicle and Honda SMART Key stops after turning the ignition switch to the (On) position. It is probably caused by the following:

- Strong radio waves or noise are affecting the system
- You lose the Honda SMART Key while riding

However, this does not affect the operation of your vehicle until stop the engine except the idling stop.

If you turn the ignition switch to the SEAT FUEL, (Off) or (Lock) position while the Honda SMART Key indicator is flashing, the ignition switch ring, turn signals and the Honda SMART Key indicator will come on for about 20 seconds, automatically go off, and then the ignition switch will lock.

**KO type** The buzzer also rings at this time.



To stop this flashing and ringing, press and hold the ignition switch for more than 2 seconds. After the flashing and ringing stop, the ignition switch is locked.

If you do not have the Honda SMART Key, the ignition switch can be unlocked in another way. ■ P. 138

### Fuel Gauge Failure Indication

If the fuel system has an error, the fuel gauge indicators will be displayed as shown in the illustrations.

If this occurs, see your dealer as soon as possible.



## When the Idling Stop System Does Not Operate Properly

### Idling Stop Indicator Does Not Come On

When the Idling Stop indicator does not come on, perform the followings.

If the Idling Stop switch is at  (Idling):

Press the Idling Stop switch to  (Idling Stop).

If the engine is cold:

Warm up the engine.

The Idling Stop system does not operate when the engine is cold.


If you did not ride the vehicle after engine starts:

Ride the vehicle at speeds of over 10 km/h (6 mph). The Idling Stop system does not operate until you ride once.

If PGM-FI malfunction indicator lamp (MIL) lights:

When the PGM-FI malfunction indicator lamp (MIL) lights, the Idling Stop system does not operate for protection of the engine. See your dealer.

If the battery voltage is low:

Ride the vehicle awhile, then stop the engine and then restart the engine with start button referring to the starting procedure ( P. 73) for standard engine starting. The Idling Stop system may not operate if the battery voltage is low.

If this occurs frequently, contact your dealer.

## Engine is Not Stopped by the Idling Stop System While the Idling Stop Indicator is On

---

When the engine is not stopped by the Idling Stop system while the Idling Stop indicator is on, perform the followings.

### **If the vehicle does not stop completely:**

Stop the vehicle completely. The Idling Stop system operates if the speed is only at 0 km/h (0 mph).

### **If the throttle is not closed completely:**

Close the throttle completely.




## Engine Does Not Start Even If the Throttle is Opened


Engine does not start even if the throttle is opened, perform the followings.

### If the side stand is down:

While the engine is stopped by the Idling Stop system, if you operate the side stand, the flashing Idling Stop indicator turns off or stops flashing and stays on, and the Idling Stop system is cancelled. Restart the engine with start button referring to the starting procedure (▶ P. 73) for standard engine starting.

### If the Idling Stop switch is at (Idling):

While the engine is stopping by the Idling Stop system, if you press the Idling Stop switch to  (Idling), the Idling Stop system will be cancelled. Restart the engine with start button referring to the starting procedure (▶ P. 73) for standard engine starting.

If the Idling Stop indicator flashes (the Idling Stop switch is at  (Idling Stop) position), but engine does not start even if the throttle is opened, perform the followings.

### Low (or dead) battery or battery lead is loose:

Check the battery and battery terminals. If the battery is weak, contact your dealer.

## When the Honda SMART Key System Does Not Operate Properly

When the Honda SMART Key system does not work properly, perform the following.

- Check that the Honda SMART Key system is activated.

Lightly push the ON/OFF button on the Honda SMART Key.

If the Honda SMART Key LED is red, activate the Honda SMART Key system.

📖 P. 48

If the Honda SMART Key LED does not respond, replace the battery.

- Check that there is no communication failure in the Honda SMART Key system. The Honda SMART Key system uses low-intensity radio waves. The Honda SMART Key system may not work properly in the following conditions:

- ▶ When there are facilities nearby that generate strong radio waves or noise such as TV towers, power stations, radio stations, or airports.
- ▶ When you carry the Honda SMART Key with a laptop or wireless communication device such as a radio or mobile phone.
- ▶ When the Honda SMART Key comes into contact with or is covered by metal objects.

## When the Honda SMART Key System Does Not Operate Properly

- Check that a registered Honda SMART Key is used.  
Use a registered Honda SMART Key.  
The Honda SMART Key system cannot be activated without a registered Honda SMART Key.
- Make sure that you do not use a broken Honda SMART Key.  
If you use a broken Honda SMART Key, the Honda SMART Key system cannot be activated. Bring the emergency key and ID tag to your dealer.

- Check the battery condition and battery lead in your vehicle.  
Check the battery and battery terminals. If the battery is weak, contact your dealer.

If the Honda SMART Key system cannot be activated due to other causes, contact your dealer.

# Unlock the Seat in an Emergency


The seat lock can be unlocked by using the emergency key.

## Open

1. Remove the front lid. ➤ P. 105
2. Align the projection of the emergency key with the slot of the emergency seat opener, and turn the emergency key counterclockwise.
3. Open the seat and turn the emergency key clockwise

## Close

1. Close and push down on the rear of the seat until it locks. Make sure that the seat is locked securely by pulling it up lightly. If the seat is not locked, turn the emergency key clockwise to lock the seat catch.
2. Install the front lid.





# Unlock the Ignition Switch in an Emergency

## Set up to ID number input mode

1. Press and hold the ignition switch for more than 4 seconds.
  - ▶ The ignition switch ring and the Honda SMART Key indicator flash.
2. Check the ID number on the ID tag.
3. Press the ignition switch while the ignition switch ring and the Honda SMART Key indicator are flashing.
  - ▶ The ignition switch ring and the Honda SMART Key indicator stay lit, and the ID number input mode turns on.



## ID number input


You can input your ID number by pressing the ignition switch when the ignition switch is  (Off),  (Lock) and SEAT FUEL position. Input the ID number on the ID tag in order from the left in turn by pressing the ignition switch. The ID number is authenticated according to the number of times the ignition switch is pushed.

Push the ignition switch the desired number of times within 5 seconds when the ignition switch ring comes on. After 5 seconds, the ignition switch ring goes off and comes on again. This means that the inputted number is fixed, and you can input the next number.

- ▶ If the ignition switch ring does not come on in blue, the battery may be low. Contact your dealer.

## Example:

- To input "0", wait for 5 seconds without pushing the ignition switch when the ignition switch ring comes on.
- To input "1", push the ignition switch once within 5 seconds when the ignition switch ring comes on.



## ID number input success

After the last ID number is input, the ignition switch ring and the Honda SMART Key indicator go off, and when they come on again the ignition switch is unlocked.

Turn the ignition switch to the **I** (On) position within 6 minutes. You can start the engine.

To lock the ignition switch, turn the ignition switch to the SEAT FUEL, **O** (Off), or **L** (Lock) position, and press and hold the ignition switch for 2 seconds. The ignition switch also locks automatically when the ignition switch has been in the SEAT FUEL, **O** (Off), or **L** (Lock) position for about 6 minutes after the ID number is successfully inputted.

When the ignition switch is locked, the ignition switch ring goes off.

To unlock the ignition switch again, repeat the procedure for unlocking the ignition switch.

## Unlock the Ignition Switch in an Emergency

### ID number input failure

After the last ID number is input, the ignition switch ring and the Honda SMART Key indicator flash at 1 second intervals, and then go off.

The ignition switch does not unlock.

Redo the "Unlock the Ignition Switch in an Emergency" procedure. ➤ P. 138

### ID number input cancel

If you make a mistake while inputting your ID, do not press the ignition switch, just wait for the ignition switch ring and the Honda SMART Key indicator to turn off.

Redo the "Unlock the Ignition Switch in an Emergency" procedure. ➤ P. 138

Repairing a puncture or removing a wheel requires special tools and technical expertise. We recommend you have this type of service performed by your dealer.

After an emergency repair, always have the tyre inspected/replaced by your dealer.

### Emergency Repair Using a Tyre Repair Kit

---

If your tyre has a minor puncture, you can make an emergency repair using a tubeless tyre repair kit.

Follow the instructions provided with the emergency tyre repair kit.

Riding your vehicle with a temporary tyre repair is very risky. Do not exceed 50 km/h (30 mph). Have the tyre replaced by your dealer as soon as possible.

### **WARNING**

Riding your vehicle with a temporary tyre repair can be risky. If the temporary repair fails, you can crash and be seriously injured or killed.

If you must ride with a temporary tyre repair, ride slowly and carefully and do not exceed 50 km/h (30 mph) until the tyre is replaced.



### Battery Goes Dead

---

Charge the battery using a motorcycle battery charger.

Remove the battery from the vehicle before charging.

Do not use an automobile-type battery charger, as these can overheat a motorcycle battery and cause permanent damage. If the battery does not recover after recharging, contact your dealer.

#### NOTICE

Jump starting using an automobile battery can damage your vehicle's electrical system and is not recommended.

### Burned-out Light Bulb

---



All light bulbs on the vehicle are LEDs. If there is an LED which is not turned on, see your dealer for servicing.

The headlight/front turn signal lights/position lights/brakelights/taillights/rear turn signal lights/license plate light use several LEDs. If there is a LED which is not turned on, see your dealer for servicing.

## Blown Fuse

Before handling fuses, see "Inspecting and Replacing Fuses." ► P. 96

### Fuse Box Fuses



## Electrical Trouble ► Blown Fuse

1. Remove the battery cover. ► P. 104
2. Open the fuse box cover.
3. Pull the main fuse and other fuses out one by one with the fuse puller located inside of the fuse box cover. Check for a blown fuse. Always replace a blown fuse with a spare fuse of the same rating.
4. Install the fuse box cover.
5. Install the battery cover.

### NOTICE

If a fuse fails repeatedly, you likely have an electrical problem. Have your vehicle inspected by your dealer.

## Unstable Engine Operation Occurs Intermittently

If the fuel pump filter is clogged, unstable engine operation will occur intermittently while riding.

Even if this symptom occurs, you can continue to ride your vehicle.

If unstable engine operation occurs even if sufficient fuel is available, have your vehicle inspected by your dealer as soon as possible.

# Information

Service Diagnostic Recorders .....	P. 147
Keys.....	P. 147
Instruments, Controls, & Other Features...	P. 151
Caring for Your Vehicle.....	P. 152
Storing Your Vehicle.....	P. 156
Transporting Your Vehicle .....	P. 157
You & the Environment .....	P. 158
Serial Numbers .....	P. 159
Fuels Containing Alcohol .....	P. 160
Catalytic Converter .....	P. 161

## Service Diagnostic Recorders

Your vehicle is equipped with service-related devices that record information about powertrain performance and riding conditions. The data can be used to help technicians diagnose, repair and maintain the vehicle. This data may not be accessed by anyone else except as legally required or with the permission of the vehicle owner.

However this data may be accessed by Honda, its authorised dealers and authorised repairers, employees, representatives and contractors only for the purpose of the technical diagnosis, research and development of the vehicle.


## Keys

### Emergency Key

The emergency key is used for an emergency.

- To unlock the seat. ➤ P. 137

Do not store the emergency key in any compartment.



### Honda SMART Key

Carrying the Honda SMART Key allows you to perform the following operations:

- Locking or unlocking the ignition switch
- Releasing the seat lock
- Opening the fuel lid
- Locking or unlocking the steering

The ID number of the Honda SMART Key is on the ID tag. You can also unlock the ignition switch by inputting the ID number.

Always carry both the emergency key and ID tag, but separate from the Honda SMART Key, to avoid losing all of them at the same time.

Also store a copy of your ID number in a safe place other than your vehicle.

The Honda SMART Key contains electronic circuits. If the circuits are damaged, the Honda SMART Key will not allow you to perform any operations.

- Do not drop the Honda SMART Key or set heavy objects on them.
- Protect the Honda SMART Key from direct sunlight, high temperature, and high humidity.
- Do not scratch or puncture.
- Do not store near any magnetized products such as a magnetized key chain.
- Always keep the Honda SMART Key away from electric appliances such as a TV, radio, PC or low-frequency massage device.
- Keep the Honda SMART Key away from liquids. If it gets wet, dry it immediately with a soft cloth.
- Keep the Honda SMART Key away from the vehicle while washing the vehicle.
- Do not burn.
- Do not wash in an ultrasonic cleaner.

- If fuel, wax, or grease adhere to the Honda SMART Key, wipe it off immediately to avoid cracking or warping.
- Do not disassemble the Honda SMART Key other than when changing a battery. Only the cover of the Honda SMART Key can be disassembled. Do not disassemble other parts.
- Do not lose your Honda SMART Key. If you lose it, you will need to register a new Honda SMART Key. See your dealer with your emergency key and ID tag for registration.

The battery in the Honda SMART Key system normally lasts about 2 years.

Do not keep mobile phones or other radio transmitting devices in any compartment. The radio frequency from the devices will interrupt the Honda SMART Key system.

To get an additional Honda SMART Key, take the Honda SMART Key and the vehicle to your dealer.

### EU Directive

This Honda SMART Key system complies with the RE (Radio Equipment) Directive (2014/53/EU).




The declaration of conformity to RE Directive is provided to the owner at the time of purchase. The declaration of conformity should be kept at a safe place. When the declaration of conformity is lost or is not provided, contact your dealer.

### Korea only

신청자명칭 : Honda Lock Mfg. Co., Ltd.  
 기자재 명 칭 : Smart system  
 기본모델명 : HLSS-6A, HLSS-6B  
 제조자 : Honda Lock Mfg. Co., Ltd.  
 제조국가 : Vietnam





# Instruments, Controls, & Other Features

## Ignition Switch

Leaving the ignition switch in the **I** (On) position with the engine stopped will drain the battery.

Do not turn the ignition switch while riding.

## Odometer

The display locks at 999,999 when the read-out exceeds 999,999.

## Tripmeter

The tripmeter returns to 0.0 when the read-out exceeds 9,999.9.

## Document Bag

The owner's manual, registration, and insurance information can be stored in the plastic document bag located underside of the seat.

## Caring for Your Vehicle

Frequent cleaning and polishing is important to ensure the life of your Honda. A clean vehicle makes it easier to spot potential problems. In particular, seawater and salts used to prevent ice on roads promote the formation of corrosion. Always wash your vehicle thoroughly after riding on coastal or treated roads.

### Washing

Allow the engine, muffler, brakes, and other high-temperature parts to cool before washing.

1. Rinse your vehicle thoroughly using a low pressure garden hose to remove loose dirt.
2. If necessary, use a sponge or a soft towel with mild cleaner to remove road grime.
  - ▶ Clean the windscreen, headlight lens, panels, and other plastic components with extra care to avoid scratching them. Avoid directing water into the air cleaner, muffler, and electrical parts.

3. Thoroughly rinse your vehicle with plenty of clean water and dry with a soft, clean cloth.
4. After the vehicle dries, lubricate any moving parts.
  - ▶ Make sure that no lubricant spills onto the brakes or tyres. Brake discs, pads, drum or shoes contaminated with oil will suffer greatly reduced braking effectiveness and can lead to a crash.
5. Apply a coat of wax to prevent corrosion.
  - ▶ Avoid products that contain harsh detergents or chemical solvents. These can damage the metal, paint, and plastic on your vehicle.  
Keep the wax clear of the tyres and brakes.
  - ▶ If your vehicle has any matte painted parts, do not apply a coat of wax to the matte painted surface.

## **I Washing Precautions**

Follow these guidelines when washing:

- Do not use high-pressure washers:
    - ▶ High-pressure water cleaners can damage moving parts and electrical parts, rendering them inoperable.
    - ▶ Water in the air intake can be drawn into the throttle body and/or enter the air cleaner.
  - Do not direct water at the muffler:
    - ▶ Water in the muffler can prevent starting and causes rust in the muffler.
  - Dry the brakes:
    - ▶ Water adversely affects braking effectiveness. After washing, apply the brakes intermittently at low speed to help dry them.
  - Do not direct water under the seat:
    - ▶ Water in the under seat compartment can damage your documents and other belongings.
- 
- Do not direct water at the air cleaner:
    - ▶ Water in the air cleaner can prevent the engine from starting.
  - Do not direct water near the headlight:
    - ▶ The headlight's inside lens may fog temporarily after washing or while riding in the rain. This does not impact the headlight function.  
However, if you see a large amount of water or ice accumulated inside the lens(es), have your vehicle inspected by your dealer.
  - Do not use wax or polishing compounds on mat painted surface:
    - ▶ Use a soft cloth or sponge, plenty of water, and a mild detergent to clean mat painted surfaces. Dry with a soft clean cloth.

### Aluminium Components

Aluminium will corrode from contact with dirt, mud, or road salt. Clean aluminium parts regularly and follow these guidelines to avoid scratches:

- Do not use stiff brushes, steel wool, or cleaners containing abrasives.
- Avoid riding over or scraping against curbs.

### Panels

Follow these guidelines to prevent scratches and blemishes:

- Wash gently using a soft sponge and plenty of water.
- To remove stubborn stains, use diluted detergent and rinse thoroughly with plenty of water.
- Avoid getting petrol, brake fluid, or detergents on the instruments, panels, or headlight.

## Windscreen

Using plenty of water, clean the windscreen with a soft cloth or sponge. (Avoid using detergents or any kind of chemical cleaner on the windscreen.) Dry with a soft, clean cloth.

### NOTICE

To avoid possible scratching or other damage, use only water and a soft cloth or sponge to clean the windscreen.

For a dirtier windscreen, use a diluted neutral detergent with a sponge and plenty of water. Make sure to wash off all the detergent. (Detergent residue may cause windscreen cracks.)

Replace the windscreen if scratches cannot be removed and they obstruct clear vision.

Take care to keep battery electrolyte, brake fluid, or other chemical solvents off the windscreen and screen garnish. They will damage the plastic.

## Exhaust Pipe and Muffler

When the exhaust pipe and muffler are painted, do not use a commercially available abrasive kitchen cleaning compound. Use a neutral detergent to clean the painted surface on the exhaust pipe and muffler. If you are not sure if your exhaust pipe and muffler are painted, contact your dealer.

## Storing Your Vehicle

If you store your vehicle outdoors, you should consider using a full-body cover.

If you won't be riding for an extended period, follow these guidelines:

- Wash your vehicle and wax all painted surfaces (except matte painted surfaces). Coat chrome pieces with rust-inhibiting oil.
- Place your vehicle on its centre stand and position a block so that both tyres are off the ground.
- After rain, remove the body cover and allow the vehicle to dry.
- Remove the battery (➡ P. 103) to prevent discharge. Fully charge the battery and then place it in a shaded, well-ventilated area.
  - ▶ If you leave the battery in place, disconnect the negative ⊖ terminal to prevent discharge.

After removing your vehicle from storage, inspect all maintenance items required by the Maintenance Schedule.

## Transporting Your Vehicle

If your vehicle needs to be transported, it should be carried on a motorcycle trailer or a flatbed truck or trailer that has a loading ramp or lifting platform, and motorcycle tie-down straps. Never try to tow your vehicle with a wheel or wheels on the ground.

**NOTICE**

Towing your vehicle can cause serious damage to the transmission.



## You & the Environment

Owning and riding a vehicle can be enjoyable, but you must do your part to protect the environment.

### Choose Sensible Cleaners

Use a biodegradable detergent when you wash your vehicle. Avoid aerosol spray cleaners that contain chlorofluorocarbons (CFCs) which damage the atmosphere's protective ozone layer.

### Recycle Wastes

Put oil and other toxic wastes in approved containers and take them to a recycling centre. Call your local or state office of public works or environmental services to find a recycling centre in your area, and to get instructions on how to dispose of non-recyclable wastes. Do not place used engine oil in the trash, or pour it down a drain or on the ground. Used oil, petrol, coolant, and cleaning solvents contain poisons that can hurt refuse workers and contaminate drinking water, lakes, rivers, and oceans.



## Serial Numbers

The frame and engine serial numbers uniquely identify your vehicle and are required in order to register your vehicle. They may also be required when ordering replacement parts.

The frame number is stamped at the back on the right side of the frame.

You can check it from below at the back on the right side of the vehicle.

You should record these numbers and keep them in a safe place.



## Fuels Containing Alcohol

Some conventional fuels blended with alcohol are available in some locales to help reduce emissions to meet clean air standards. If you plan to use blended fuel, check that it is unleaded and meets the minimum octane rating requirement.

The following fuel blends can be used in your vehicle:

- Ethanol (ethyl alcohol) up to 10% by volume.
  - ▶ Petrol containing ethanol may be marketed under the name Gasohol.

The use of petrol containing more than 10% ethanol may:

- Damage the painting of the fuel tank.
- Damage the rubber tubes of the fuel line.
- Cause corrosion of the fuel tank.
- Cause poor drivability.

### NOTICE

Use of blended fuels containing higher than approved percentages can damage metal, rubber, plastic parts of your fuel system.

If you notice any undesirable operating symptoms or performance problems, try a different brand of petrol.

## Catalytic Converter

This vehicle is equipped with a three-way catalytic converter. The catalytic converter contains precious metals that serve as catalysts in high temperature chemical reactions that convert hydrocarbons (HC), carbon monoxide (CO), and oxides of nitrogen (NOx) in the exhaust gasses into safe compounds.

A defective catalytic converter contributes to air pollution and can impair your engine's performance. A replacement unit must be an original Honda part or equivalent.

Follow these guidelines to protect your vehicle's catalytic converter.

- Always use unleaded petrol. Leaded petrol will damage the catalytic converter.
- Keep the engine in good running condition.
- Have your vehicle serviced if your engine is misfiring, backfiring, stalling, or otherwise not running properly, stop riding and turn off the engine.

# Specifications

## ■ Main Components

Overall length	1,935 mm (76.2 in)	
Overall width	740 mm (29.1 in)	
Overall height	1,105 mm (43.5 in)	
Wheelbase	1,315 mm (51.8 in)	
Minimum ground clearance	135 mm (5.3 in)	
Caster angle	26° 30'	
Trail	<b>ED type</b>	79 mm (3.1 in)
	<b>KO type</b>	80 mm (3.1 in)
Curb weight	130 kg (287 lb)	
Maximum weight capacity *1	<b>ED type</b>	180 kg (397 lb)
	<b>KO type</b>	160 kg (353 lb)
	13 kg (29 lb)	
Maximum luggage weight *2	Centre compartment	10 kg (22 lb)
	Front box	1.0 kg (2.2 lb)
	Rear carrier	5 kg (11 lb)
Passenger capacity	Rider and 1 passenger	
Minimum turning radius	1.90 m (6.2 ft)	

\*1 : Including rider, passenger, all luggage, and accessories.

\*2 : Includes the weight of the luggage and added accessories.

Displacement	125 cm <sup>3</sup> (7.6 cu-in)
Bore x stroke	53.5 x 55.5 mm (2.11 x 2.19 in)
Compression ratio	11.5:1
Fuel	Unleaded petrol Recommended: 91 RON or higher
Fuel containing alcohol	ETHANOL up to 10 % by volume
Tank capacity	8.1 L (2.14 US gal, 1.78 Imp gal)
Battery	<b>ED type</b>
	YTZ8V
	12 V-7.0 Ah (10 HR) / 7.4 Ah (20 HR)
	<b>KO type</b>
	GTZ8V
	12 V-7.0 Ah (10 HR)
Primary reduction	V-Matic (2.65:1-0.81:1)
Final reduction	10.352

## ■ Service Data

Tyre size	Front	110/70-14M/C 50P
	Rear	130/70-13M/C 63P
Tyre type		Bias-ply, tubeless
Recommended Tyres	<b>ED type</b>	Front MICHELIN CITY GRIP
		Rear MICHELIN CITY GRIP
	<b>KO type</b>	Front IRC SCT-006
		Rear IRC SCT-007
Tyre category of use *1	Normal	Permitted
	Special	Not Permitted
	Snow	Not Permitted
	Moped	Not Permitted
Tyre air pressure (Drivers only)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	225 kPa (2.25 kgf/cm <sup>2</sup> , 33 psi)
Tyre air pressure (Driver and passenger)	Front	200 kPa (2.00 kgf/cm <sup>2</sup> , 29 psi)
	Rear	250 kPa (2.50 kgf/cm <sup>2</sup> , 36 psi)
Spark plug	(standard)	LMAR8L-9 (NGK)
Spark plug gap		0.8 - 0.9 mm (0.03 - 0.04 in)
Idle speed		1,700 ± 100 rpm

\*1: EU regulation

Recommended engine oil	Honda 4-stroke motorcycle oil API Service Classification SG or higher, excluding oils marked as "Energy Conserving" or "Resource Conserving," SAE 10W-30, JASO T 903 standard MB	
	After draining 0.8 L (0.8 US qt, 0.7 Imp qt)	
Engine oil capacity	After draining & cleaning strainer screen	0.85 L (0.90 US qt, 0.75 Imp qt)
	After disassembly	0.9 L (1.0 US qt, 0.8 Imp qt)
Transmission oil capacity	After draining	0.12 L (0.13 US qt, 0.11 Imp qt)
	After disassembly	0.14 L (0.15 US qt, 0.12 Imp qt)
Recommended brake fluid		Honda DOT 3 or DOT 4 Brake Fluid
Cooling system capacity		0.50 L (0.53 US qt, 0.44 Imp qt)
Recommended coolant		Pro Honda HP Coolant

## Specifications

### ■ Bulbs

Headlight	LED
Brakelights/Taillights	LED
Front turn signal lights	LED
Rear turn signal lights	LED
License plate light	LED
Position lights	LED

### ■ Fuses

Main fuse	30 A
Other fuses	<b>WW125A</b> 15 A, 10 A, 7.5 A
	<b>WW125</b> 10 A, 7.5 A

## A

ABS (Anti-lock Brake System) .....	11, 128
ABS (Anti-lock Brake System) indicator.....	42
Accessories .....	15
Average fuel mileage meter .....	28

## B

Battery.....	94, 103
Battery Charging Condition indicator .....	41, 127
Brakes	
Brake Lever Freeplay.....	115
Fluid .....	97, 110, 112
Pad Wear.....	113, 114
Shoe Wear.....	118
Braking .....	11

## C

Catalytic Converter.....	161
Centre Compartment.....	84
Clock .....	27
Colour Label.....	93
Compartment	
Document Bag .....	151

Owner's Manual .....	151
Coolant.....	108

## D

Digital Clock Adjustment.....	33
Display Setting .....	31
Document Bag .....	84, 151

## E

Emergency	
Emergency Key.....	147
Unlock the Seat .....	137
Engine	
Number.....	159
Electrical Trouble .....	142
Environment .....	158

## F

Flooded Engine .....	73
Frame Number .....	159
Front Box .....	85



**Fuel**

Gauge .....	27
Recommended .....	78
Remaining .....	27
Tank Capacity .....	78

<b>Fuses</b> .....	96, 143
--------------------	---------

**G**

<b>Gasohol</b> .....	160
----------------------	-----

**H**

<b>Hazard Switch</b> .....	44
<b>Headlight Dimmer Switch</b> .....	44
<b>Helmet Holder</b> .....	83
<b>High Beam Indicator</b> .....	40
<b>High Coolant Temperature Indicator</b> .....	40
<b>Honda SMART Key</b> .....	148
<b>Honda SMART Key Indicator</b> .....	41
<b>Honda SMART Key System</b> .....	47
<b>Horn Button</b> .....	44

**I**

<b>Idling Stop Indicator</b> .....	40
<b>Idling Stop Switch</b> .....	44

<b>Idling Stop System</b> .....	69
---------------------------------	----

**Ignition Cut-off System**

Side Stand .....	119
------------------	-----

<b>Ignition Switch</b> .....	45, 151
------------------------------	---------

<b>Image Labels</b> .....	6
---------------------------	---

<b>Indicators</b> .....	40
-------------------------	----

<b>Instruments</b> .....	26
--------------------------	----

**K****Key**

Emergency Key .....	147
Honda SMART .....	47

**L**

<b>Labels</b> .....	6
---------------------	---

<b>Load Limits</b> .....	16
--------------------------	----

<b>Loading Guidelines</b> .....	16
---------------------------------	----

**M****Maintenance**

Fundamentals .....	92
Importance .....	88
Safety .....	88
Schedule .....	89

Maximum Weight Limit.....	16, 162
Modifications.....	15

## O

Odometer.....	28, 151
Oil	
Engine.....	96, 106
OIL CHANGE indicator.....	29
Overheating.....	126

## P

Parking.....	12
Parts Location.....	20
Petrol.....	14, 78, 162
PGM-FI (Programmed Fuel Injection)	
Malfunction Indicator Lamp (MIL)....	40, 127
Protective Apparel.....	10

## R

Rear Carrier.....	86
Recommended	
Coolant.....	98
Fuel.....	78
Oil.....	96

Refuelling.....	78
-----------------	----

## Removal

Battery.....	103
Battery Cover.....	104
Front Lid.....	105

Repair Kit.....	141
-----------------	-----

Riding Precautions.....	11
-------------------------	----

## S

Safety Precautions.....	10
Seat.....	82
Serial Numbers.....	159
Side Stand.....	119
Side Stand Ignition Cut-off System....	73, 119
Specifications.....	162
Speedometer.....	27
Start Button.....	44
Starting the Engine.....	73

**Storage**

Centre Compartment.....	84
Equipment .....	82
Front Box.....	85
Owner's Manual .....	84, 151
Rear Carrier .....	86
Tool Kit.....	84

<b>Storing</b> .....	156
----------------------	-----

<b>Switches</b> .....	44
-----------------------	----

**T**

<b>Throttle</b> .....	120
-----------------------	-----

<b>Tool</b> .....	102
-------------------	-----

<b>Torque Control</b> .....	28
-----------------------------	----

<b>Torque Control indicator</b> .....	42
---------------------------------------	----

<b>Torque Control OFF indicator</b> .....	42
---	----

<b>Transporting</b> .....	157
---------------------------	-----

<b>Tripmeter</b> .....	28, 151
------------------------	---------

<b>Troubleshooting</b> .....	124
------------------------------	-----

<b>Turn Signal Indicators</b> .....	41
-------------------------------------	----

<b>Turn Signal Switch</b> .....	44
---------------------------------	----

**Tyres**

Air Pressure .....	99, 163
--------------------	---------

Puncture.....	141
---------------	-----

Replacing .....	99
-----------------	----

**V**

<b>V-BELT indicator</b> .....	30
-------------------------------	----

**W**

<b>Warning Indicator On</b> .....	127
-----------------------------------	-----

<b>Washing Your Scooter</b> .....	152
-----------------------------------	-----

<b>Weight Limit</b> .....	16
---------------------------	----